



SANSWITCH-10910

10-Port 10/100 Mbit Switch
8PoE-Port, 1 Uplink Port

PRODUCT DESCRIPTION

► Application:

This switch offer 10-Port 10Base-T/100Base-TX (Fast Ethernet) that lead you to a fast ethernet connection. Users are now able to transfer high bandwidth-demanded files faster and get a real efficiency.

► Technical specifications:

| | |
|--------------------------------|-------------------------|
| Type | PoE Switch |
| Number of Ethernet ports | 8x PoE + 2xLAN (Uplink) |
| Power over Ethernet (PoE) | Yes |
| Number of PoE ports | 8 |
| PoE standard | IEEE 802.3af |
| Max. PoE Output Voltage (port) | 15,4 W / 30W (1x CH) |
| Max. PoE power consumption | 120 W |
| Ethernet standards | 10Base-TX/100Base-TX |
| Ethernet connector | RJ-45 |
| Managed | No |
| Flow control | Yes IEEE 802.3x |
| Supported protocols | CSMA/CD |
| VLAN | No |
| QoS (quality of service) | No |
| Integrated web interface | No |
| Weight | 2,5 kg |
| Voltage | 100 - 240 V AC |
| Operating temperature (°C) | 0 to +55 |
| Rel. humidity (%) | 10 - 90, non-condensing |
| Rack mount (U) | 1 |
| Fan | No |

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

| | |
|-------------------------------|-------------------------|
| Max. Power consumption (watt) | 150 |
| Dimensions WxHxD (mm) | 220mm*160mm*35mm |
| Identifier | CE, FCC, RoHS |
| Items included in delivery | Power cord, 19" bracket |
| Specials | Noiseless |

► Recommended Accessories

| | |
|--------------|-------------------------------|
| NWK-P3.05ES2 | 3m Patchkabel CAT5e, SF/UTP |
| NWK-P0.55ES2 | 0,5m Patchcabel CAT5e, SF/UTP |