



SANSWITCH-20910

10Port Switch Gigabit, PoE,
8xPoE- + 2xUplink, RJ45, 15.4W/30W

PRODUCT DESCRIPTION

► Application:

This switch offer 8-Ports 10Base-T/100Base-TX/1000Base-TX PoE ports and 2x 10Base-T/100Base-TX/1000Base-TX (Gigabit)uplink ports that lead you to a real gigabit connection. Users are now able to transfer high bandwidth-demanded files faster and get a real efficiency.

► Technical specifications:

Type	PoE Switch
Number of Ethernet ports	8x PoE + 2xLAN (Uplink)
Power over Ethernet (PoE)	Yes
Number of PoE ports	8
PoE standard	IEEE802.3at / IEEE802.3af
Max. PoE Output Voltage (port)	15,4 W / 25,4 W
Max. PoE power consumption	150 W
Number of gigabit ports	10
Ethernet standards	10Base-T/100Base-TX/1000Base-TX
Ethernet connector	RJ-45
Managed	No
Flow control	Yes IEEE 802.3x
Supported protocols	CSMA/CD
VLAN	No
QoS (quality of service)	No
Integrated web interface	No
Weight	2,5 kg
Voltage	100 - 240 V AC
Operating temperature (°C)	-20 to +55
Rel. humidity (%)	10 - 90, non-condensing

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Rack mount (U)	1
Fan	No
Max. Power consumption (watt)	180
Dimensions WxHxD (mm)	220 x 160x 35
Identifier	CE, FCC, RoHS
Items included in delivery	Power cord
Specials	Noiseless

► Recommended Accessories

NWK-P0.55ES2	0,5m Patchcabel CAT5e, SF/UTP
NWK-P3.05ES2	3m Patchkabel CAT5e, SF/UTP