

NUUO®



SCB-C24

NUUO 16-Channel Digital Output RS-485
for NUUO Systems

PRODUCT DESCRIPTION

► Application:

SCB-C24 provides 16 optical isolated digital output channels that allow you to output open collector signal to driven your devices on RS485 network. All channel features screw terminals for convenient connection of field signals as well as LED's to indicate channel status. All inputs are equipped with photo- couplers to protect the module against high voltage spikes and ground potential differences.

► Technical specifications:

Type	Digital output
USB standard	-
Digital inputs	-
Digital outputs	16 Digital outputs
RS-485 interface	Yes, 1x
RS-485 Baud rate (max. bps)	115200
RS-232 signal	-
RS-422 signal	-
RS-485 signal	-
Transmission distance	up to 1200 m
LEDs	Power on, all output channels
Power via USB	-
Watchdog	Host status
Power supply	Screw terminal or external DC adapter
Max. Power consumption (watt)	1.5
Dimensions WxHxD (mm)	151 x 75 x 26

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.