


NUUO®



SCB-C28

NUUO 4-Channel Digital input/output
for NUUO Systems

PRODUCT DESCRIPTION

► Application:

SCB-C28 provides with 4 optical isolated digital input channels and 4 power relays output. All channel features screw terminals for convenient connection of field signals as well as LED's to indicate channel status. SCB-C28 can be easily control by SCB-C08.

► Technical specifications:

Type	Digital input/output
USB standard	-
Digital inputs	4 digital input channel
Digital outputs	4 digital output channel
RS-485 interface	Yes
RS-485 Baud rate (max. bps)	115200
RS-232 signal	-
RS-422 signal	-
RS-485 signal	-
Transmission distance	500 m
LEDs	Power on, all input channels
Power via USB	-
Watchdog	Host Status
Power supply	Screw terminal or external DC adapter
Max. Power consumption (watt)	2.7
Dimensions WxHxD (mm)	151x75x26

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.