



SFC-244KSIA

25x IR outdoor Speeddome
Supports AHD/CVI/TVI/CVBS (960H)

PRODUCT DESCRIPTION

► Application:

SANTEC HD CVI speed dome for indoor and outdoor use according to IP-66.

► Technical specifications:

Type	SFC-Speeddome
Video signal	AHD/CVI/TVI/CVBS(FBAS)
Sensor	1/2,8"
Sensor type	1/2.8" Progressive Scan Exmor CMOS
Horizontal resolution (TVL)	1080p / 720p / 1000 TVL CVBS
Effective pixel	1920x1080
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	> 55dB
Lens mount	Intern
Iris control	DC
Lens type	Motor zoom lens
Focal length	4,8 mm - 120 mm
Angle of view (horizontal)	59.2° - 2.4° (HD-Mode)
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0,05 lux (color) / 0 lux (IR on), 0.005 lux (b/w)
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	Ultra 2DNR / 3DNR
Shutter (sec.)	1/3 - 1/100,000
White balance	Auto / ATW / indoor / outdoor / manual

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Backlight compensation	120 dB True WDR, BLC, HLC
Wide dynamic range (WDR)	DWDR
Day/night mode adjustment	Auto / color / B/W
Camera adjustments	OSD
Auto focus	Yes
Optical zoom	25x, adjustable
Digital zoom	16x
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Motion detection (zones)	Yes
Privacy zones	Yes, 24
Camera title	Yes
Audio	Yes
Audio in-/outputs	1 / 0
Audio codec	G.711a / G.711Mu / PCM
Rotation radius	360° Endless
Rotation speed	0,1° to 300°/s.
Preset speed	Pan: 0.1-200°/s, Tilt:0.1-120°/s
Tilt angle (°)	-15° bis 90° (Auto Flip 180°)
Number of presets	300
Tours	8
Pattern	5
Video output	BNC, 75 Ohm 1 Vpp
Switch input contacts	2
Switch output contacts	1
Control interface	RS-485, HDCVI (coax)
Control protocols	Pelco D/P and more
Self-test function	Yes
Classification	IP-66
Installation	Wall mount and pole mount
Housing colour	White / black
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR range (m)	up to 100
Wavelength LED	850 nm
IR-LED illuminant	6
Voltage	12 V DC
Max. Power consumption (watt)	9,6; max. 23.2W (IR on, PTZ)
DORI max.	1612m - 646m - 323m - 161m
(Detect-Observe-Recognize-Identify)	
Operating temperature (°C)	-30 bis +65
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxT (mm)	160 x 295.4 mm

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Weight	3.0 kg
Identifier	CE, RoHS
Items included in delivery	Wandarm
Specials	Coaxtransmission up to 700m

► Note:

1-channel BNC HDCVI high definition video output / CVBS standard definition video output (can switch). Power supply already included in delivery.

► Weitere Bilder:



► Recommended Accessories

SNCA-CM-4670	Corner Mount Adapter for see recommended accessories
SNCA-PM-4660	Pole Mount adapter up to 127 mm and SNCA-JB-4640 and SNCA-WM-4642 (SNC-211RSIA)
SNCA-JB-4640	Junction box for dome cameras
SNCA-CMT-4852	Ceiling Mount for SANTEC IP Speed-Dome
SNCA-EXT-4852	Extension for SNCA-CMT-4852
KSC-USB-NET	USB Keyboard for SCVR und SNVR recorders, analog. and IP domes
BWPS-DC12V5A	Stabilized 12Vdc power supply, max. 5A inkl. Kaltgerätestecker