NEW



SML-2212

SANTEC 22" CCTV 6 in 1 plastic-monitor, 1920x1080, 60Hz, CVBS,CVI,TVI,AHD,VGA,HDMI

PRODUCT DESCRIPTION

Application:

The new monitors of the SML series have a timeless design and are equipped with professional technology

Technical specifications:

Туре	Lcd monitor
Screen diagonal	21.5" (54.6 cm)
Video signal	PAL, NTSC
Resolution pixel	1920x1080
Pixel dot pitch (mm)	0.2482(H) x 0.2482(V)
Resolution	FUIIHD
Picture format	16:9
Colours	16.7M
Brightness (cd/m2)	250
Contrast ratio	1000:1
Refresh rate (ms)	5
Visible area (H/V) mm	476.64(H) x 268.11(V)
View angle R/L and U/D in $^{\circ}$	88/88 - 75/75
Operating Frequency	30-85 KHz(H) / 50-75Hz(V)
Background lighting	LED
Video inputs	No
Video outputs	No
PC video input	VGA, HDMI
HDMI Version	HDMI-1->2.0
POP (picture-on-picture) function	No
BURG-GUARD GmbH	

Wormgermühle, 58540 Meinerzhagen, Germany Tel.: +49 2358 905 490, Fax: +49 2358 905 499 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Technical specifications:

PIP (picture-in-picture) function	No
Audio inputs	2x 3.5 mm (phone jack) (BNC-IN/PC-IN)
Speakers	2x 3W
OSD menu languages	Multi language
Control OSD	Buttons on rear side
Classification	IP-40
Installation option	VESA / MIS-D 75x75
Housing colour	Black
Housing material	Plastic
Voltage	12 V DC using external power supply 230VAC/2A
Max. Power consumption (watt)	20
Operating temperature (°C)	-10 to +50
Rel. humidity (%)	20 - 70, non-condensing
24/7 operation	Yes
Dimensions WxHxD (mm)	490,93 x 293,18 x 38,80 (without bracket)
Dimensions mounting stand	250,1 x 61,1 x 149,1
WxHxD (mm)	
Weight	2,1 Kg
Identifier	CE
Items included in delivery	Power supply 12VDC

Weitere Bilder:





Recommended Accessories

VA-3240	LCD-Monitor wall mount black/silver up to 24", max. wall dist. 537mm, max.
	load 32 kg
VA-VESA-172	VESA wall mount for LCD-monitors 7,5x7,5 to 20x20cm, Walldist. 11cm
HDMI-700-E	HDMI Extender Transmission via UTP up to 60m
KVM-HD150	Full HD HDMI extender, Cat5e up to 150m Übertragung per CAT5e/6 bis zu
	150m

BURG-GUARD GmbH Wormgermühle, 58540 Meinerzhagen, Germany Tel.: +49 2358 905 490, Fax: +49 2358 905 499 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.