



### **SML-3222Q**

SANTEC 32" 4K metal monitor 3840x2160, 60Hz, 4x HDMI+ 1x DP

# PRODUCT DESCRIPTION

# Application:

The SANTEC SML-3222Q 4K / UHD Monitor is specially designed to connect multiple HDMI devices, such as Recorder. With 32 "(81.2 cm) and a resolution of 3840x2160 pixels, this monitor delivers a perfect UHD video quality. Thanks to the 16: 9 format, LED backlight technology and 4x HDMI + 1x DP connection, the monitor is versatile to working in any professional field.

### ▶ Technical specifications:

Туре	Lcd monitor
Screen diagonal	32" (81.2 cm)
Video signal	PAL, NTSC
Resolution pixel	3840x2160
Pixel dot pitch (mm)	0.1845 (H) x 0.1845 (V)
Picture format	16:9
Colours	1.07G
Brightness (cd/m2)	350
Contrast ratio	1400:1
Refresh rate (ms)	5
Visible area (H/V) mm	708.48(H)x398.52(V)
View angle R/L and U/D in °	85/85 - 80/80
Operating Frequency	30-145 KHz(H) / 24-120Hz(V)
Background lighting	LED
Video inputs	No
Video outputs	No
PC video input	4x HDMI, 1x DP

BURG-GUARD GmbH

Wormgermühle, 58540 Meinerzhagen, Germany Tel.: +49 2358 905 490, Fax: +49 2358 905 499 BURG-GUARD@burg.biz, www.burg-guard.com



# ► Technical specifications:

HDMI Version	HDMI-1->2.0, HDMI-2-4 -> 1.4
Displayport version	1.2
POP (picture-on-picture) function	Yes
PIP (picture-in-picture) function	Yes, 1 2, 1/2, 1-4
Audio outputs	3.5 mm (phone jack)
Speakers	2x 5W
OSD menu languages	Multi language
Control OSD	Buttons on right site
Classification	IP-40
Installation option	VESA / MIS-E 200x200
Housing colour	Black
Housing material	Metal
Voltage	100-240VAC / 47-63Hz
Max. Power consumption (watt)	55
Operating temperature (°C)	-10 to +50
Rel. humidity (%)	20 - 70, non-condensing
24/7 operation	Yes
Dimensions WxHxD (mm)	731,4 x 432,5 x 49 (without mounting)
Dimensions mounting stand	45 x 64,7 x 160
WxHxD (mm)	
Weight	15 Kg
Identifier	CE, FCC, RoHS
Items included in delivery	remote control, HDMI cable,power cord,QIG

#### Note:

Available at the end of May

### ► Weitere Bilder:



## **▶** Recommended Accessories

HDMI-700-E HDMI Extender Transmission via UTP up to 60m

KVM-HD150 Full HD HDMI extender, Cat5e up to 150m Übertragung per CAT5e/6 bis zu

150m

VA-VESA-172 VESA wall mount for LCD-monitors 7,5x7,5 to 20x20cm, Walldist. 11cm

BURG-GUARD GmbH Wormgermühle, 58540 Meinerzhagen, Germany Tel.: +49 2358 905 490, Fax: +49 2358 905 499 BURG-GUARD@burg.biz, www.burg-guard.com

