



SML-4322Q

SANTEC 43" 4K metal monitor
3840x2160, 60Hz, 4x HDMI + 1x DP

PRODUCT DESCRIPTION

► Application:

The SANTEC SML-4322Q 4K / UHD Monitor is specially designed to connect multiple HDMI devices, such as Recorder. With 32 "(81.2 cm) and a resolution of 3840x2160 pixels, this monitor delivers a perfect UHD video quality. Thanks to the 16: 9 format, LED backlight technology and 4x HDMI + 1x DP connection, the monitor is versatile to working in any professional field.

► Technical specifications:

| | |
|-----------------------------|------------------------------|
| Type | Lcd monitor |
| Screen diagonal | 43" (109,2 cm) |
| Video signal | PAL, NTSC |
| Resolution pixel | 3840x2160 |
| Pixel dot pitch (mm) | 0.1845 (H) x 0.1845 (V) |
| Picture format | 16:9 |
| Colours | 1.07G |
| Brightness (cd/m2) | 350 |
| Contrast ratio | 1400:1 |
| Refresh rate (ms) | 5 |
| View angle R/L and U/D in ° | 85/85 - 80/80 |
| Operating Frequency | 30-145 KHz(H) / 24-120Hz(V) |
| Background lighting | LED |
| Video inputs | No |
| Video outputs | No |
| PC video input | 4x HDMI, 1x DP |
| HDMI Version | HDMI-1->2.0, HDMI-2-4 -> 1.4 |

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

| | |
|---|---|
| Displayport version | 1.2 |
| POP (picture-on-picture) function | Yes |
| PIP (picture-in-picture) function | Yes, 1 2, 1/2, 1-4 |
| Audio outputs | 3.5 mm (phone jack) |
| Speakers | 2x 5W |
| OSD menu languages | Multi language |
| Control OSD | Buttons on right site |
| Classification | IP-40 |
| Installation option | VESA / MIS-E 200x200 |
| Housing colour | Black |
| Housing material | Metal |
| Voltage | 100-240VAC / 47-63Hz |
| Max. Power consumption (watt) | 65 |
| Operating temperature (°C) | -10 to +50 |
| Rel. humidity (%) | 20 - 70, non-condensing |
| 24/7 operation | Yes |
| Dimensions WxHxD (mm) | 965 x 575 x 70 (without mounting) |
| Dimensions mounting stand WxHxD (mm) | 45 x 60 x 180 |
| Weight | 22,7 |
| Identifier | CE, FCC, RoHS |
| Items included in delivery | remote control, HDMI cable, power cord, QIG |

► Weitere Bilder:



► Recommended Accessories

| | |
|-------------|---|
| HDMI-700-E | HDMI Extender Transmission via UTP up to 60m |
| KVM-HD150 | Full HD HDMI extender, Cat5e up to 150m Übertragung per CAT5e/6 bis zu 150m |
| VA-VESA-172 | VESA wall mount for LCD-monitors 7,5x7,5 to 20x20cm, Walldist. 11cm |

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.