

SNPS-12D5A9K

SANTEC Sammelnetzteil zur Versorgung von bis zu 9 Kameras, 12V DC, 5A

PRODUCT DESCRIPTION

Application:

Multiple power supply to support devices with 12 V DC. Maximum current is 5 A. Outputs PTC fused is rated to 0.55 A. If you want to support several devices with 12 V DC, this power supply unit would be ideal. This power supply is used for wall mounting.

Technical specifications:

Туре	Multiple power supply
Input voltage	230 V AC
Output voltage	12 V DC / 5 A
Output	9 x Screwed terminal, PTC fused
Housing colour	White
Housing material	Metal
Operating temperature (°C)	- 20 to +45
Storage temperature (°C)	-40 to +60
Rel. humidity (%)	20 - 80
Dimensions WxHxD (mm)	165x165x50mm
Weight	900g
Identifier	CE
Specials	Wall mount, locked
Output Efficiency	>82%



BURG-GUARD GmbH Wormgermühle, 58540 Meinerzhagen, Germany Tel.: +49 2358 905 490, Fax: +49 2358 905 499 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Weitere Bilder:





Recommended Accessories

BURG-GUARD GmbH Wormgermühle, 58540 Meinerzhagen, Germany Tel.: +49 2358 905 490, Fax: +49 2358 905 499 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.