



SNPS-12D5S9

SANTEC multiple power supply
to support up to 9 cameras, 12V DC, 5A

PRODUCT DESCRIPTION

► Application:

Multiple power supply to support devices with 12 V DC. Maximum current is 5 A. Outputs PTC fused is rated to 0.55 A. If you want to support several devices with 12 V DC, this power supply unit would be ideal. This power supply is used for wall mounting.

► Technical specifications:

Type	Multiple power supply
Input voltage	230 V AC
Output voltage	12 V DC / 5 A
Output	9 x Screwed terminal, PTC fused
Housing colour	Beige
Housing material	Metal
Operating temperature (°C)	-30 to +45
Storage temperature (°C)	-40 to +60
Rel. humidity (%)	20 - 80
Dimensions WxHxD (mm)	255x90x210
Weight	2 kg
Identifier	CE, FCC, RoHs, UL
Items included in delivery	Power cord
Specials	Wall mount
Output Efficiency	>82%
Fuse Type	0.55 A (PTC)

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Recommended Accessories

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.