



VCA-24V-8A16P

SANTEC 24 V AC Multiple power supply
24 V AC / 8A, 16 PTC-fused screwd outputs

PRODUCT DESCRIPTION

► Application:

Multiple power supply to support devices with 24 V AC. Maximum current is 8 A. Outputs PTC fused rated 1.1A If you want to support several devices with 24 V AC, this power supply unit would be ideal. This power supply is used for wall mounting.

► Technical specifications:

Type	Multiple power supply
Input voltage	230 V AC
Output voltage	24 V AC, 8 A
Output	16 x Screwed terminal, PTC fused
Housing colour	White
Housing material	Metal
Operating temperature (°C)	-10 to +45
Rel. humidity (%)	20 - 80
Dimensions WxHxD (mm)	224x200x60
Weight	4 kg
Identifier	CE
Specials	Wall mount

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Recommended Accessories

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.