



## WVT-881

Wireless video transmission device  
Outdoor 5G Wireless video

### PRODUCT DESCRIPTION

#### ► Application:

WVT-881 is a "high performance" for video optimized rf-IP transmission system for outdoor use. Using 5 GHz frequencies.

#### ► Technical specifications:

Type	Wireless video transmission device
Operating Frequency	5745~5825MHz
Max. range (clear view)	up to 3 km (300Mbps)
max. RF output	27 dBm
Bandwidth Mbps	up to 300Mbps, max. 40Mbps at 3km
Wireless Direction Angle (H° / V°)	40° / 15°
VLAN	Yes, IEEE 802.1Q (Port & Tagged based)
Encryption Type	WEP/WPA-PSK/WPA2/CCMP(AES)/TKIP
Number of Ethernet ports	2
Ethernet	10/100 BaseT auto sensing
Wireless Mode	Access Point, Client, WDS Client, WDS Access Point
Network mode	Bridge-Mode, Router-Mode
Point Base	Point to Point or Point to Multipoint
Security features	IP/MAC Filter, hide network name
Supported protocols	TCP/UDP/ARP/ICMP/DHCP/HTTP/NTP(SNMP)
PoE standard	No (24VDC PoE)
Max. Power consumption (watt)	8
Dimensions WxHxD (mm)	80x280x30
Weight	0,45 kg

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

**► Technical specifications:**

Pole diameter (mm)	40-60
Operating Temperature	-30° to +70°C
Rel. humidity (%)	Max. 95, non-condensing
Items included in delivery	incl.PoE PS, pole mount bracket, power cable
Specials	2 devices are necessary, Poe Injector

**► Note:**

To use the system, it is necessary to use two system, point to point or point to multipoint.

**► Weitere Bilder:****► Recommended Accessories**

NWK-P3.05ES2	3m Patchkabel CAT5e, SF/UTP
NWK-P0.55ES2	0,5m Patchcabel CAT5e, SF/UTP