



World's Best Graffiti Coating

An extremely DURABLE and LONG LASTING, PROTECTIVE coating for brick, stone, masonry, timber and natural building surfaces

Product Data Sheet

Product Code: WB0070

Issued: August 8, 2016

PRODUCT DESCRIPTION


World's Best Graffiti Coating (WBGC) is a water-based all-weather, long-term SACRIFICIAL protection, formulated for most types of surfaces. Provides durable protection against spray paint, marker / felt tip pens pollution and grime. Also provides protection against salt and sea-type moisture.

Correctly applied, life expectancy against graffiti is generally 7 years but it can be effective up to 10 years.

This protective coating is permeable and allows the surface to breathe. Prevents graffiti from penetrating the substrate.

The surface must be re-protected following graffiti removal which can be done immediately to a damp (not wet) surface.


WBGC is readily biodegradable according to OECD test 302 B.




Historic Buildings



Decorative Sound Walls




Feature Walls



Wooden Fences



Split Face / Cinderblock



Natural Stone

FEATURES & BENEFITS

- Safe, quick and easy to apply by spray, brush or roller.
- Fast drying time.
- Makes getting graffiti off walls a pleasure.
- Virtually invisible / matte finish



FEATURES & BENEFITS cont...

- Nontoxic and virtually odorless.
- Ideal for heritage buildings.
- Can be used on porous and nonporous substrates.

INSTRUCTIONS FOR USE

Preparation

Clean off both graffiti and other contamination, such as road grime, grease, wax, oil and paint residue etc. from the substrate.

It is normal best practice to mask and protect windows in a suitable manner.

Exterior Protection

Shake or stir the product well before use. WBGC can be applied with any of the following: rollers, paint brush, low-pressure sprayers or airless sprayers. Two coats are usually applied.

NOTE: Allow some intermediate drying between coats.

WBGC can be applied to a damp, not wet surface. Runs and/or excessive application can easily be washed off with water, following completion of work.

**FOR EXPERT TECHNICAL ADVICE ON YOUR JOB,
PLEASE CALL 1-818-247-2555 OR
EMAIL SALES@GRAFFITIREMOVALINC.COM**



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. The SDS contain information that you will need to protect yourself, your employees and customers against health or safety hazards associated with our products. URG US INC requires that you obtain a copy of the respective SDS prior to using or transporting our products. The information in this Product Data Sheet is based on data that we believe to be reliable and is offered in good faith, but without guarantee, and subject to the terms and conditions set forth in URG US INC's Product Data Sheet and any additional documentation provided by URG US INC's, as ultimately the conditions and methods of the use of URG US INC's products are beyond URG US INC's control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com



World's Best Graffiti Coating

An extremely DURABLE and LONG LASTING, PROTECTIVE coating for brick, stone, masonry, timber and natural building surfaces


Product Data Sheet

Product Code: WB0070

Issued: August 8, 2016



Handheld Pump-up Sprayer



High Volume Low Pressure Sprayer (HVLP)



Airless Sprayer

Interior Protection

Some painted substrates can be protected using a roller or with a low-pressure spray in combination with a brush or roller. The protection is applied three times.

APPLICATION

Use the product as provided. Do not dilute. Walls can be dampened during hot weather to assist application.

This product information is intended as a guide for the use of this product. Urban Restoration Group US Inc. cannot give any guarantee for result achieved. The applicator of the product shall carry out testing and be responsible for the result.

COVERAGE GUIDELINES

Varies depending upon the porosity of surface material.

- Concrete, brick or similar: approx. 500 sq ft (46.5 sq m) per gal per coat.
- Limestone, sandstone, plaster or other soft absorbent surfaces: approx. 360 sq ft (35 sq m) per gal per coat.
- Painted surfaces: approx. 640 sq ft (60 sq m) per gal per coat

2 coats are recommended.

Drying Period

The protected surface will be water and graffiti-resistant after 2 hours and dry after 4 hours. Ultimate protection will be achieved after 72 hours.

Appearance on surface

Transparent, mostly invisible dependent on type of surface. UV-resistant. Weather / water / graffiti resistant.

Before commencing large scale use always test first to ensure finish is satisfactory. Some building materials could darken or become shiny.

EXTERIOR GRAFFITI REMOVAL

Method 1: Normal substrate.

Remove graffiti with hot water and high pressure (~ 90°C / 200°F & 90-50 bar / 1300-2175 psi). For faster removal, use World's Best Graffiti Removers in conventional manner. Re-protect cleaned area.




Filled-in bubble writing on previously coated masonry wall.



Graffiti is removed using just hot water at 2000 PSI / 2-3 gal per minute.



Blue spray can on pre-coated random wall. Brush on BBSM.



Rinse with cold water.



Once clean, re-apply WBGC.

INTERIOR GRAFFITI REMOVAL

Removal from Painted Substrate

Brush on SENSITIVE SURFACE REMOVER to small areas at a time and wipe off with a damp cloth completing each area before proceeding further. Re-apply WORLD'S BEST COATING.



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. The SDS contain information that you will need to protect yourself, your employees and customers against health or safety hazards associated with our products. URG US INC requires that you obtain a copy of the respective SDS prior to using or transporting our products. The information in this Product Data Sheet is based on data that we believe to be reliable and is offered in good faith, but without guarantee, and subject to the terms and conditions set forth in URG US INC's Product Data Sheet and any additional documentation provided by URG US INC's, as ultimately the conditions and methods of the use of URG US INC's products are beyond URG US INC's control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com



World's Best Graffiti Coating

An extremely DURABLE and LONG LASTING, PROTECTIVE coating for brick, stone, masonry, timber and natural building surfaces

Page 3 of 3

Product Data Sheet

Product Code: WB0070

Issued: August 8, 2016

INTERIOR GRAFFITI REMOVAL cont...

Removal from Porous Substrate

Apply SENSITIVE SURFACE REMOVER. Rinse off with hot water and wet-vac.

Re-protection of Cleaned Surface

When removing graffiti, the protective coating is also normally removed. Re-apply 2 coats of WBGC.

TEMPERATURE USAGE

Ideal temperature for external application should be between 45°-95°F / 8°-35°C. Minimum temperature is 40°F.

Relative humidity must not exceed 95%.

NB: Fresh concrete has to cure for at least 28 days before protection.

TECHNICAL DATA

Composition

Water carried paraffin wax dispersion.

5-10% solid contents.

Properties

Color: White.

Odor: Odorless.

PH: 8

Storage: Store in a frost-free environment in original container.

Shelf Life: Approximately 3 years.

Precaution: Use protective clothing and gloves.

DOT Markings: Not classified as dangerous.

See SDS for further information.

LEGAL DISCLAIMER

Read and follow label directions and observe all safety precautions in the use of this product. Because conditions of product use are outside of our control and vary widely,

the following is made in lieu of all express or implied warranties: This product will conform to Urban Restoration Group US, Inc.'s published product specifications and be free from defects in material and manufacture on the date of purchase.

Except where prohibited by law, Urban Restoration Group US Inc., further disclaims, and shall not be liable for any incidental, special, consequential or indirect loss or damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced, regardless of the legal theory asserted.

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS PRODUCT AND MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, URBAN RESTORATION GROUP US, INC'S LIABILITY SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF THE PRODUCT PURCHASED.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of Urban Restoration Group US, Inc. products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. Urban Restoration Group US, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

If this product is defective upon your receipt, your exclusive remedy shall be, at Urban Restoration Group US, Inc.'s option, to replace the product or refund the purchase price of the Urban Restoration Group US, Inc. product.

CONTACT MANUFACTURER

Urban Restoration Group US Inc.
5439 San Fernando Rd. W., Los Angeles CA 90039 USA
Tel: +1-818-247-2555. Fax: +1-818-247-2515
Email: sales@graffitiremovalinc.com
Web: www.graffitiremovalinc.com

Revised: September 11, 2023



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. The SDS contain information that you will need to protect yourself, your employees and customers against health or safety hazards associated with our products. URG US INC requires that you obtain a copy of the respective SDS prior to using or transporting our products. The information in this Product Data Sheet is based on data that we believe to be reliable and is offered in good faith, but without guarantee, and subject to the terms and conditions set forth in URG US INC's Product Data Sheet and any additional documentation provided by URG US INC's, as ultimately the conditions and methods of the use of URG US INC's products are beyond URG US INC's control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com