

OXOS® 2060N

OxOs® 2060N is a virgin 20x60 mesh granular adsorbent produced from animal bone by a high temperature activation process under stringent quality control. It has limited surface area, very good mechanical hardness and hydroxyapatite mineral content that make it ideal for removal of certain heavy metals in many liquid phase applications.

SPECIFICATIONS

US Standard Sieve Mesh Size:	20x60 (0.85 mm x 0.25 mm)
> 20 mesh (0.85 mm), %	5 maximum
< 60 mesh (0.25 mm), %	5 maximum
Moisture (as packed), %	5 maximum

TYPICAL PROPERTIES

Apparent density (g/cc)	0.64 typical
pH	8 – 10 typical

Standard packing is 25kg (55-lb.) bags or 500kg (1100-lb.) bulk sacks.
All test methods are ASTM procedures where applicable.

This information has been gathered from standard reference materials and/or test data that are assumed to be accurate and reliable. Oxbow Activated Carbon LLC makes no warranties or representations with respect to this product except as may be set forth in purchase and sale documentation relating to this product. Oxbow Activated Carbon LLC makes no other warranties of any kind, either expressed or implied, in connection with this product, including but not limited to any warranty of merchantability or fitness for a particular purpose or application. Buyer assumes all liability and risk that may arise from the use of this product. Oxbow Activated Carbon LLC reserves the right to modify product properties without prior notification.



EXPERIENCE OXBOW ACTIVATED CARBON'S DEDICATED CUSTOMER SUPPORT
+1 760.630.5724 | sales@oxbowactivatedcarbon.com
2535 Jason Court Oceanside, CA 92056 USA

www.oxbowactivatedcarbon.com