



Omnipure

1904 Industrial Way
Caldwell, Idaho 83605

E-mail: sales@omnipure.com

Phone: 1-800-398-0833 or 208-454-2597

Fax: 208-454-0026

Item # Q5505, Q-Series 2.5 X 10" sediment

The Q-Series is the ultimate "user friendly" inline filter on the market. Replacement is as easy as unscrewing the filter body from the permanent head and screwing in the replacement. The Q-Series is also available with the optional Twist Tap in-head valve system, which automatically turns the supply water off when the body is disconnected from the head. No tools. No drips. No hassles. The Q-Series is available in 2.5" diameter, and in lengths of 6", 8", 10", 12" and 14".

Sizes shown include 10"



[+ more](#)

[Specifications](#) | [General Installation / Operation / Maintenance Requirements](#) | [Special Notices](#) | [Additional Information](#)

Specifications

Flow Rate	0.5 gpm
Maximum Operating Pressure	125 psig
Operating Temperature	2 to 38 °C 35 to 100 °F
Rated Capacity	Dependent upon the quality of the influent water

Reduction Claim	Dirt, sand, and sediment reduction
Filter Diameter	2.5 in
Available Lengths	6 in 8 in 10 in 12 in 14 in
Available Thread Size	1/8 in 1/4 in
Thread Type	National Pipe Thread (NPT) - Female
Filter Head Type	Non-Valved Valved

General Installation / Operation / Maintenance Requirements

- Note flow direction of filter.
- For quick connect fittings, push scratch free tube end that has been cleanly and squarely cut into the fitting until it bottoms. Threaded fittings must be wrapped with PTFE tape before installation. Install PTFE taped fittings and tighten firmly. Use two wrenches to firmly tighten tubing.
- Flush new cartridge with 5 gallons of water prior to use and check for leaks. If leaks occur, check tightness of tubing and fittings. If leaks persist, discontinue use and call your supporting dealer.
- Replace cartridge when rated capacity is reached, or when flow becomes too slow.
- Install in compliance with state and local laws and regulations.

Special Notices

- The contaminants or other substances removed or reduced by this water treatment system are not necessarily in your water.
- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Additional Information

Standard media includes granular activated carbon for taste and odor reduction, polypropylene depth filtration for removal of grit and sediment, and polyphosphate to control lime and scale deposits. Also, a wide variety of specialty and custom media options are available as well as a corresponding RO membrane body for use in reverse osmosis systems. Eliminates taste and odor. Filters out sediment. Protects equipment.

The Q-Series is designed to give our customers a high quality, economically priced alternative to similar products on the market. Our engineering and production expertise enables us to offer both the initial unit and the replacement bodies at a significantly lower price than the competition. The Q-Series is produced with a diameter of 2.5 in and lengths of 6 in, 8 in, 10 in, 12 in and 14 in. Quick-Connect 1/4 in fittings are available on this series. Female threads are available in 1/4 in and 3/8 in NPT.

Water filter heads sold separately.