Bulletin Number: TB817465 Effective: January 2010

FUJIFILM TECHNICAL BULLETIN Replaces Bulletin Dated: February 2004

Reversal Bath & Replenisher

For Processing Fujichrome and Process E-6 Compatible Color Reversal Films

Catalog Number: 600005442 (10 x 8 L)

DESCRIPTION

This product is a Process E-6 reversal bath replenisher. The product is designed for use in all equipment processing color reversal films compatible with Process E-6.

SAFE HANDLING INSTRUCTIONS

Please refer to Material Safety Data Sheets (MSDS) for specific chemical details. For emergencies, please contact CHEMTREC at 1-800-424-9300. You can obtain an MSDS by calling the Fujifilm Technical Hotline at 1-800-526-0851 Ext. 10.

HMIS INFORMATION

Hazardous Materials Identification System. Please refer to Section 3 in the MSDS for further information.

	Concentrate	Replenisher	Working Tank
Health	1	1	1
Flammability	0	0	0
Reactivity	0	0	0
Personal Protection	С	С	С

SPECS & RECOMMENDATIONS

Temperature	24° – 39.4° C 75° – 103° F		
Processing Time	2'00" Spec (1'00" – 4'00" Spread)		
Starting Replenishment Rate	Dilution Rate	1:19	1:24
	per ft²	100 ml	200 ml
	per m²	1076 ml	2152 ml
	per roll 135-24	42 ml	84 ml
	per roll 120	54.7 ml	109 ml
	per roll 220	109 ml	218 ml
	per 4x5	13.9 ml	27.8 ml

SPECIFIC GRAVITY & pH

or zon to chattii i a pri					
		SpG @ 25° C		SpG @ 38° C	
	pH @ 25° C	Dilute 1:19	Dilute 1:24	Dilute 1:19	Dilute 1:24
Repl. Tank	5.75 ± 0.05	1.009 ± 0.003	1.006 ± 0.003	1.007 ± 0.003	1.004 ± 0.003
Fresh Tank	5.75 ± 0.05	1.009 ± 0.003	1.006 ± 0.003	1.007 ± 0.003	1.004 ± 0.003
Season Tank	5.87 ± 0.05	1.010 ± 0.003	1.008 ± 0.003	1.007 ± 0.003	1.005 ± 0.003

MIXING INSTRUCTIONS - REPLENISHER

	8 L @ 1:19	Dilution	10 L @ 1:24 Dilution		
R	Water 68° – 86° F (20° – 30° C) Concen- trate		Water 68°- 86° F (20°- 30° C)	Concen- trate	
8 or 10 Liters	7.6 L	400 ml 1 Bottle	9.6 L	400 ml 1 Bottle	
1 Liter	950 ml	50 ml	960	40	
1 Gallon	121.6 oz	6.4 oz	122.9 oz	5.1 oz	

To Mix 8 Liters of Replenisher at 1:19 (1 part concentrate to 19 parts water)

- Start with 7.5 liters of warm water.
- Add 1 bottle of concentrate. Rinse bottle with 100 ml of water and add to mix tank. Mix using 20 strokes or until uniform.

Do Not Over Mix.

To Mix 10 Liters of Replenisher at 1:24 (1 part concentrate to 24 parts water)

- Start with 9.5 liters of warm water.
- Add 1 bottle of concentrate. Rinse bottle with 100 ml of water and add to mix tank. Mix using 20 strokes or until uniform.

Do Not Over Mix.

MIXING INSTRUCTIONS – WORKING TANK

Warm Water		Concentrate	
1 Liter	950 ml	50 ml	
1 Gallon	121.6 oz	6.4 oz	
Tank Volume			
YOUR TANK			

To calculate the amount of water and reversal bath concentrate that you will need, multiply your tank volume by each of the numbers listed, in either liters or gallons. For example, if you have a 10 liter tank, 10x950 ml = 9.50 liters of water and 10x50 ml = 500 ml of reversal bathconcentrate.

 $1000 \text{ ml} = 1 \text{ liter} \quad 128 \text{ oz} = 1 \text{ gallon}$

FOR BLENDER SETTINGS AND ADDITIONAL REPLENISHMENT RATES, PLEASE REFER TO **BULLETIN PRO6 PROCESS SPECIFICATIONS**

SHELF LIFE

	Concentrate	Mixed Replenisher	Working Tank		
Time	U = 18 Months O = 2 Weeks	2 Weeks	2 Weeks		
Color	Clear, Yellowish	Clear, Pale Yellow	Clear, Pale Yellow		
Odor	Slight Musty Odor	Slight Musty Odor	Slight Musty Odor		

U = Unopened, O = Opened

The data contained in this photographic bulletin is believed to be true and accurate, but is offered solely for your consideration, investigation, and verification. Nothing herein shall be construed to be a warranty or guarantee by either FUJIFILM Hunt Chemicals, Inc. or any of its affiliates, and all such warranties, implied or otherwise, including any implied warranty of merchantability, are hereby expressly disclaimed. You, of course, are fully responsible for any use and / or domestic or foreign sale of the product(s) described, and nothing in this photographic bulletin shall be construed to constitute permission or a recommendation to practice any invention covered by patent or patent application or know-how owned by FUJIFILM, its affiliates, or others.