






# EMMA

Design MONICA ARMANI

Supporting structure in powder coated 304 stainless steel tube. Seat with powder-coated aluminum frame and hand-woven rope in synthetic fiber, seat cushion and backrest padded with Dryfeel foam for outdoor use. Suspended version with support rope.

 <p><b>23696</b> <b>Nido Nest</b></p> <p>istruzioni d'uso using instruction <b>123696</b></p> <p>telo copertura cover <b>9486C</b></p> <p>MODELLO REGISTRATO REGISTERED MODEL</p>		<p><b>GAMBE LEGS</b></p> <ul style="list-style-type: none"> <li>Bianco White</li> <li>Grigio Seta Silk Grey</li> <li>Denim Denim</li> <li>Ruggine Rust</li> <li>Bronzo Metal Metal Bronze</li> <li>Verde Green</li> <li>Grigio Grey</li> <li>Moka Dark Brown</li> <li>Nero Black</li> <li>Legno Wood</li> <li>Irako</li> </ul> <p><b>ALUMINIO ALUMINIUM</b></p> <p><b>TEST ART.</b> <b>23696</b></p> <p>Requisiti generali di sicurezza EN 581-1   TEST SUPERATO - NESSUN DIFETTO Carico statico su sedile e schienale EN 1728+AC   TEST SUPERATO - NESSUN DIFETTO Resistenza a fatica sedile e schienale EN 1728+AC   TEST SUPERATO - NESSUN DIFETTO</p> <p>General security requirements EN 581-1   TEST PASSED - NO DEFECTS Static load on seat and backrest EN 1728+AC   TEST PASSED - NO DEFECTS Backrest and seat fatigue resistance EN 1728+AC   TEST PASSED - NO DEFECT</p>	<p><b>INTRECCIO WEAVING</b></p> <ul style="list-style-type: none"> <li>VARBROPE Beige</li> <li>VARBROPE Ruggine</li> <li>VARBROPE Dark Grey</li> </ul> <table border="1"> <thead> <tr> <th colspan="4">collo base</th> </tr> <tr> <th>Pz</th> <th>L</th> <th>P</th> <th>H</th> </tr> </thead> <tbody> <tr> <td rowspan="2">1</td> <td>94</td> <td>104</td> <td>20</td> </tr> <tr> <td>37</td> <td>41</td> <td>7 7/8</td> </tr> <tr> <td colspan="4">m<sup>3</sup> 0,196 - Kg 18,2 tot.</td> </tr> <tr> <td colspan="4">Kg 13,2 net</td> </tr> <tr> <th colspan="4">collo stelo</th> </tr> <tr> <th>Pz</th> <th>L</th> <th>P</th> <th>H</th> </tr> <tr> <td rowspan="2">1</td> <td>176</td> <td>95</td> <td>102</td> </tr> <tr> <td>69 1/4</td> <td>37 3/8</td> <td>40 1/8</td> </tr> <tr> <td colspan="4">m<sup>3</sup> 1,705 - Kg 19,7 tot.</td> </tr> <tr> <td colspan="4">Kg 15,4 net</td> </tr> <tr> <th colspan="4">collo cesta c/cuscino</th> </tr> <tr> <th>Pz</th> <th>L</th> <th>P</th> <th>H</th> </tr> <tr> <td rowspan="2">1</td> <td>97</td> <td>75</td> <td>119</td> </tr> <tr> <td>38 1/4</td> <td>29 1/4</td> <td>46 7/8</td> </tr> <tr> <td colspan="4">m<sup>3</sup> 0,866 - Kg 21,1 tot.</td> </tr> <tr> <td colspan="4">Kg 14,0 net</td> </tr> </tbody></table>	collo base				Pz	L	P	H	1	94	104	20	37	41	7 7/8	m <sup>3</sup> 0,196 - Kg 18,2 tot.				Kg 13,2 net				collo stelo				Pz	L	P	H	1	176	95	102	69 1/4	37 3/8	40 1/8	m <sup>3</sup> 1,705 - Kg 19,7 tot.				Kg 15,4 net				collo cesta c/cuscino				Pz	L	P	H	1	97	75	119	38 1/4	29 1/4	46 7/8	m <sup>3</sup> 0,866 - Kg 21,1 tot.				Kg 14,0 net			
collo base																																																																								
Pz	L	P	H																																																																					
1	94	104	20																																																																					
	37	41	7 7/8																																																																					
m <sup>3</sup> 0,196 - Kg 18,2 tot.																																																																								
Kg 13,2 net																																																																								
collo stelo																																																																								
Pz	L	P	H																																																																					
1	176	95	102																																																																					
	69 1/4	37 3/8	40 1/8																																																																					
m <sup>3</sup> 1,705 - Kg 19,7 tot.																																																																								
Kg 15,4 net																																																																								
collo cesta c/cuscino																																																																								
Pz	L	P	H																																																																					
1	97	75	119																																																																					
	38 1/4	29 1/4	46 7/8																																																																					
m <sup>3</sup> 0,866 - Kg 21,1 tot.																																																																								
Kg 14,0 net																																																																								
<p><b>23697</b> <b>Nido sospeso Swing Nest</b></p>  <p><b>Set corda (8 metri) completo di ferramenta. (VEDI SCHEMA MONTAGGIO) Ferramenta di fissaggio parte alta non fornita.</b> Hanging rope (8 meters) with hardware included. (SEE ASSEMBLY SCHEME) Anchoring system not included.</p> <p><b>cuscino seduta e 1 cuscino schienale inclusi</b> seat cushion and 1 back included 1 pz - art. 2725 (50x30)</p>	<table border="1"> <thead> <tr> <th colspan="4">collo cesta c/cuscino</th> </tr> <tr> <th>Pz</th> <th>L</th> <th>P</th> <th>H</th> </tr> </thead> <tbody> <tr> <td rowspan="2">1</td> <td>97</td> <td>75</td> <td>119</td> </tr> <tr> <td>38 1/4</td> <td>29 1/4</td> <td>46 7/8</td> </tr> <tr> <td colspan="4">m<sup>3</sup> 0,866 - Kg 21,1 tot.</td> </tr> <tr> <td colspan="4">Kg 14,0 net</td> </tr> </tbody></table>	collo cesta c/cuscino				Pz	L	P	H	1	97	75	119	38 1/4	29 1/4	46 7/8	m <sup>3</sup> 0,866 - Kg 21,1 tot.				Kg 14,0 net																																																			
collo cesta c/cuscino																																																																								
Pz	L	P	H																																																																					
1	97	75	119																																																																					
	38 1/4	29 1/4	46 7/8																																																																					
m <sup>3</sup> 0,866 - Kg 21,1 tot.																																																																								
Kg 14,0 net																																																																								

## STRUCTURAL COMPONENTS

SUPPORTING STRUCTURE IN POWDER COATED 304 STAINLESS STEEL TUBE. SEAT WITH POWDER-COATED ALUMINUM FRAME AND HAND-WOVEN ROPE IN SYNTHETIC FIBER.  
**CUSHION:** QUICK DRY POLYURETHANE PADDING IN SEVERAL DENSITIES. REMOVABLE CUSHION COVER.

## CHARACTERISTICS OF THE MATERIALS

CHARACTERISTICS OF THE MATERIALS AND FABRICS ARE DESCRIBED IN THE WEBSITE [www.varaschin.it](http://www.varaschin.it) FOLDER "MATERIALS" AND YOU CAN DOWNLOAD FROM FOLDER "DOWNLOAD-MATERIALS".

## INSTRUCTIONS FOR USING THE PRODUCT PROPERLY AND SAFELY

VARASCHIN IS NOT LIABLE FOR DAMAGE CAUSED BY IMPROPER USE. THE SAME APPLIES TO DAMAGE DERIVING FROM USE IN EXTREME WEATHER CONDITIONS OR LACK OF CARE. TIPS FOR EXTENDING LONGEVITY OF COMPONENTS: DURING THE WINTER STORE IN A DRY AND CLOSED PLACE TO AVOID CONDENSATION.  
DO NOT STEP ON WITH FEET. DO NOT SWING BACK AND FORTH ON THE LEGS. DO NOT SIT ON THE BACK OR ON ARMS. DO NOT USE AS A LADDER. BUTTONS AND THE ZIPPERS OF CLOTHING MAY CAUSE DAMAGE TO THE MATERIALS. IF NECESSARY, PLEASE CONTACT VARASCHIN SPA.

## GENERAL INSTRUCTIONS FOR MAINTENANCE AND CLEANING

FOR DAILY CLEANING USE A DRY COTTON CLOTH. FOR MORE THOROUGH CLEANING USE ONLY A NEUTRAL PRODUCT DILUTED IN WARM WATER. NEVER USE ALCOHOL, AMMONIUM, THINNERS OR ABRASIVE PRODUCTS. IN MARINE ENVIRONMENTS ARTICLE SHOULD BE WEEKLY WHASED WITH FRESH WATER.  
FOR CLEANING AND TAKING CARE OF ALL MATERIALS AND FABRICS, SEE THE FOLDER "DOWNLOAD-MAINTENANCE" FROM OUR WEBSITE [www.varaschin.it](http://www.varaschin.it) OR ASK FOR IT VIA E-MAIL AT [customer@varaschin.it](mailto:customer@varaschin.it)

## GENERAL INFORMATION

N.B.: VARASCHIN SPA GUARANTEES THAT THE PRODUCT IS MADE OF QUALITY MATERIALS, USING THE BEST TECHNOLOGIES IN THE TRADE. THE COMPANY DECLINES ALL AND ANY LIABILITY FOR DAMAGE TO PERSONS AND/OR THINGS DUE TO IMPROPER USE OF THE PRODUCT. IF IN DOUBT PLEASE CONTACT THE MANUFACTURER.

## DISPOSAL

PLEASE DO NOT JUST THROW OUT THE PIECE OF FURNITURE OR ANY PART OF IT. AT THE END OF ITS USE, PROVIDE FOR THE RECYCLING OR DISPOSAL OF THE COMPONENTS IN THE APPROPRIATE AREAS.

## FIRE-FIGHTING MEASURES

ALTHOUGH THE PRODUCT IS NOT INFLAMMABLE, IT IS COMBUSTIBLE. THERE ARE NO RESTRICTIONS ON THE TYPES OF EXTINGUISHERS: POWDER, WATER, FOAM OR CO2. USE SUITABLE PROTECTION TO AVOID BREATHING IN FUMES. DURING DISPOSAL TAKE SPECIAL CARE TO PROTECT THE RESPIRATORY SYSTEM.

## PRODUCT WARRANTY

REFER TO ARTICLE 3 "PRODUCT WARRANTY" PUBLISHED ON SALES CONDITIONS, DOCUMENTS OF SALE, WEBSITE [www.varaschin.it](http://www.varaschin.it)

**TECHNICAL INFO SHEET:** This product information sheet complies with Italian Legislative Decree No. 206 of 6 September 2005, "Consumer Code".

The information given above refers to the latest data published in the price list. The company reserves the right to alter the models without notice.

COMPANY WITH SYSTEM MANAGEMENT QUALITY CERTIFIED **UNI EN ISO 9001: 2015**