

FLOS


Almendra S2 Y Short Primer, Anthracite - Specification Sheet by Patricia Urquiola, 2022

| | |
|-----------------------------------|--|
| Mounting | Ceiling Pendant |
| Lamp (Bulb) Description | LED 30W 2800lm 2700K CRI95 |
| Environment | Indoor - Dry Location |
| Dimming | 0-10V (120Vac or 277Vac) or ELV (120Vac Only) or Triac (120Vac Only) |
| Finish | Anthracite |
| Technical and Product Description | Almendra is a modular suspended lighting system providing diffused light emission, available in linear and organic leaf-like compositions. |

Each lighting unit contains an integrated Edge Lighting technology and can rotate up to a 60° angle to change the direction of the light emitted.


The product has been designed according to the International Sustainability and Carbon Certification (ISCC) standards. It is assembled without glued components so that it can be completely separated for easy recycling.

Almendra Organic: The curved module can be set to obtain multiple configurations with 2 or 3 lights in 2 lengths options, which can be positioned downwards or upwards.



● FU039633 Anthracite

Dimensional Image



ALMENDRA S2 Y SHORT

Electrical

| | |
|-----------|------|
| Voltage | 120 |
| IP Rating | IP20 |

Physical

| | |
|-----------------------|-------------------------------------|
| Construction Material | Sustainable Polycarbonate, Aluminum |
| Weight | 18 lbs |



Certifications

