

SPA FROG[®] MINERAL PURIFIER

Instructions

Specifications

- · Fits in most filters.
- Handles up to a 1000 gallon spa.
- · Lasts 4 months.
- Easy to set reminder dial for product replacement.
- To be used in conjunction with a low bromine or low chlorine support and ozone if desired.

Spa Start Up

- Always drain and refill spa every 3-4 months.
- Clean or replace filter cartridge when dirty (Follow man-

ufacturers instructions).

 Balance water according to the chart.

 Shock spa to remove all

WATER BALANCE GUIDELINES 7.2 - 7.8Total Alkalinity: 60 - 120 Calcium Hardness: 150-300 Total Dissolved Solids: <2000 Free Chlorine: .5 - 1ppm Free Bromine: 1 - 2 ppm

contaminants. (Follow manufacturers directions.)

Installing SPA FROG®

- 1. Set reminder dial on SPA FROG® to 4 months from month of installation. Turn dial with a coin.
- 2. Place SPA FROG® in one of the following locations in spa:
- a) Majority of Spas Insert SPA FROG® inside filter cartridge core (**Diagram A**). Do not allow SPA FROG® to sit too low in the filter. If blocking water flow install in filter well (Diagram B). If SPA FROG® is inside a standpipe, attach a string to the FROG® head handle for easy removal.
- b) High Flow Spas On skimmer filters with 2.5 HP or larger pump motors. place SPA FROG® outside the filter cartridge (Diagram B).
- c) Small Cartridge or Other Spas Place SPA FROG® in skimmer basket (Diagram C).

If unit is too tall, cut rod at hash marks to shorten.

Diagram A





Diagram B -High Flow Spas In Filter Well



Horizontal




Diagram C



Regular Spa Care



1. Run filtration system a minimum of four hours per day.



- 2. Regularly test water for pH, total alkalinity and chlorine or bromine levels.
- 3. Maintain a .5-1 ppm chlorine or 1-2 ppm bromine level at all times.



4. Shock the spa with a chlorine or non-chlorine shock once a week or if water looks hazy.



5. Remember to replace SPA FROG® and to drain and refill the spa every four months.

KING TECHNOLOGY, Inc.

530 11th Avenue South • Hopkins, MN 55343 952-933-6118 • FAX 952-933-2206 • www.kingtechnology.com

U.S. Patent Numbers: 6,190,547; D411,282; D422,678 and Foreign Patents Pending #20-48-0140 553110143 EPA Est. No. 071209-AZ-001

43