



BOSS • 802 Pool & Spa Silicone

TYPICAL PROPERTIES

Tensile	300
Tack-Free Time	15-20 min.
Full Cure	24 hours
Shore A Hardness	17
Modulus @ 100%, Mpa04
Movement Capability	±25%
Slump	Nil
Elongation	570%

*Information on this data sheet is subject to change without notice and should not be used for writing specifications.
For additional information on specific applications, contact Accumetric, LLC



DESCRIPTION

BOSS[®] 802 Pool & Spa Silicone is a one part, mildew resistant, acetoxycure silicone sealant. Designed for sealing spa jets, skimmers, fittings, and can be used for most repair and maintenance applications.

FEATURES

- Sealing spa jets, skimmers
- Mildew resistant
- Waterproof / weatherproof seal
- Non-sag formula
- VOC compliant in all 50 states

HOW TO USE

BOSS® 802 Pool & Spa Silicone is supplied in ready-to-use form. It flows readily from its container under pressure. A spatula or wooden paddle can be used to tool the surface.

Cure progresses inward from the surface. At conditions of 77°F (25°C) and 50% relative humidity, a tack-free skin forms within 20 minutes. Tooling should be completed within 5 to 10 minutes of application. Alternate periods of application and tooling may be required. If masking tape is used to mask an area it must be removed before the tack-free skin forms.

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use with adequate ventilation. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. Sealant releases acetic acid (vinegar-like odor) during cure. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

SHIPPING LIMITATIONS

None.

Reactive VOC 29 g/L (<3% wt)

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), BOSS® 802 Pool & Spa Silicone has a shelf life of 12 months from date of shipment. In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the nozzle tip pointed upwards. DO NOT stack cartons on their side. NEVER stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

MADE IN U.S.A.

BOSS PRODUCTS

Accumetric, LLC
350 Ring Road
Elizabethtown,
Kentucky 42701 USA
800-928-BOSS(2677)
TEL (270)769-3385
FAX (270)765-2412
Outside U.S.
TEL +1(270)769-3385
FAX +1(270)765-2412

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662)634-3060
FAX (662)634-3066

www.bossproducts.com