



Product Bulletin



TREE SAP REMOVER

Product Description:

Tree Sap Remover combines a water emulsifiable solvent with two low foaming soaps and a conditioner to remove cured and uncured tree sap, tar, bee pollen, bug residue, wax and silicone quickly and easily. Removes contaminants from painted, plastic, rubber and glass surfaces. Soft, fresh tree sap is easier to remove, but C-46-P penetrates and softens hardened tree sap so it can be easily wiped away. Safe for all exterior surfaces.

Product Details:

Ready To Use
Biodegradable
VOC Compliant
Water Base
Body Shop Safe
Phosphate Free
pH: 9.0
Color: Light Green
Fragrance: Jasmine

Packaging:

Pint: C-46-P



Features & Benefits:

Quickly Removes Cured & Uncured Tree Sap
Also Removes Tar, Bee Pollen & Bug Residue
For Use on All Painted, Plastic, Rubber and Glass Surfaces
Spray On, Wipe Off Formula

Application: *Shake well before using. Read label before use. See SDS for more information.*

If surfaces are hot, cool surface with cold water rinse before applying product.

Pretreat: The older and heavier tree sap is, the harder it will be to remove. To aid in the removal process, pre-clean as much of the cured and heavy deposits from the finish by using a plastic razor blade being careful not to scratch the finish.

Spray Tree Sap Remover on a small area, keeping the area wet. It will immediately begin to soften the tree sap. Using an applicator soaked with remover, gently rub the sap to further soften and remove it from the surface. Wipe area with a dry applicator. Repeat if necessary. After removal, wash vehicle with PRO® C-60 Super Car Wash to remove residue of tree sap and remover from the finish.

Helpful Tips:

Keep from freezing (32 °F/0 °C). Do not apply to a hot surface or let dry on surface.

Safety Data Sheet:

GHS Compliant. SDS can be found online at www.prowax.com.

BAF Industries

1451 Edinger Avenue, Suite F, Tustin, CA 92780 and Florence, KY
(800) 437-9893 • (714) 258-8055 • Fax (714) 259-1184 • www.prowax.com

