



# Wall Repair Patch Kit

Wall Repair Patch Kit consists of ready mixed drywall repair compound with high crack filling capacity in concrete, flexible self-adhesive perforated aluminum patch, grit sandpaper, and ergonomic plastic putty knife.

## Advantages:

- No mixing required, easy to use,
- High crack filling capacity,
- All the necessary equipment is in one package.
- Dries quickly to a hard finish,
- Can be varnished or painted,
- Easy to sand, can be drilled,
- Water-based non-toxic.

## Standard:

- The requirements of VOC content specifications in LEED credit EQc4.1 "Low-emitting products" of SCAQMD rule 1168.

## Usage Areas:

Wall Repair Kit is used to fill cracks, splits, holes and surface defects, and imperfections in construction materials like wood, concrete, brick, Etc.

## How to use:

Please make sure the package is filled with its contents.

The surface must be clean from all loose materials, dust, dirt, oil, and other contaminants.

Paste the patch on the surface to be fixed and press it firmly. Make sure it sticks well. Spread the repair compound on the patches using the putty knife with movement from the center to the periphery. Be sure to pour it precisely over the patch so that no voids remain.

After the repair compound is completely dry, sand the surface for a professional, smooth finish.

For increasing the curing rate, can use a hairdryer in case of need, the procedure can be repeated.

The surface can be painted on demand. Excess sealant can be removed by wet fabric materials.

## Storage and Shelf Life:

The shelf life is 18 months if stored in an unopened-original package in a dry place at temperatures between +40 °F and +80 °F.

## Safety & Disposal:

Bears no imminent risk to health. Check MSDS guidelines for disposal and further information concerning safety.



ADHESIVE & GLUES ◆ SEALANTS & SILICONES ◆ PU FOAMS ◆ AEROSOLS ◆ WATERPROOFING SYSTEMS

## Typical Properties Information

Basis	Silicone Rubber
Curing System	Acrylic Polymer
Volatile	Water
Specific Gravity	14,2 lb/gal
Skin Formation Time	10 ±5 min.
Application Temperature	+40°F to +105°F
Service Temperature	0°F to +150°F

Not suitable for use where flexibility and movement accommodation are needed. Do not apply to coated surfaces. For external applications, it must be over coated with varnish or paint to provide water resistance. Various two-part acid-catalyzed varnishes may not adhere. Preliminary test recommended before use.

## Restrictions:

Product content	Quantity
Drywall repair compound acrylic sealant	280 ml
Flexible, self-adhesive perforated patch	13,2" x 3,2"
100 Grit sandpaper	2" x 2"
Ergonomic plastic putty knife	3.5"