



WOW! Super Fast Adhesive

Wow! Super Fast Adhesive is an adhesive set that consists of high viscosity cyanoacrylate adhesive and activator, which leads to a rapid bonding experience.

Advantages:

- Extremely fast bonding,
- High bonding power,
- Suitable for use on vertical surfaces as it will not drip or slump,
- Particularly suited to difficult bond substrates that have a porous or uneven nature, it increases the bonding strength by preventing the adhesive from being absorbed by the surface.

Usage Areas:

- It is suitable for bonding a wide range of materials, including acidic surfaces and porous ones, where rapid bonding times are required.
- Suitable for MDF, wood, chip wood, rubber, most plastics, leather, and other common substrates.
- Especially suitable for the applications where cure speed needs to be accelerated.
- **Kraken Super Fast Adhesive** has a degree of gap-filling ability.
- It is recommended for use on close-fitting parts and relatively smooth surfaces.

How to use:

The surfaces of application must be clean, dry and free from all sorts of dirt and grease. Apply

the Activator on the first surface then allow it to evaporate. Apply super glue on the other surface and assemble surfaces quickly. Apply pressure a few seconds.

Clean Up:

Wipe off excess glue immediately with a dry cloth. After curing, glue residue is very difficult to remove.

If your skin contacts with the adhesive wipe off the glue with warm soapy water. Using acetone is the efficient choice but it may create skin sensitivity.

In the event of the product being sprayed into the eyes or mouth, the eyes or mouth must be kept open and rinsed with plenty of water. If necessary, seek medical advice.

Shelf Life:

12 months in unopened packaging in a dry and cool storage place at temperatures between +5°C and +25°C.

Restrictions;

- Cyanoacrylates should ideally be stored in original sealed containers until used.
- Avoid exposure to intense light and heat sources
- Cyanoacrylates can bond to the skin within seconds
- Do not drip into the skin or eyes - it can cause serious injury to your eyes.
- It will become active in a container if not closed properly.



ADHESIVE & GLUES ◆ SEALANTS & SILICONES ◆ PU FOAMS ◆ AEROSOLS ◆ WATERPROOFING SYSTEMS

- Activator is flammable. Do not throw into fire.
- Activator box is pressured. Do not crush or drill.

Properties

Glue

| | | |
|-------------------------|------------------------------------|------------|
| Glue Basis | : Ethyl Cyanoacrylate | |
| Appearance | : Liquid gel | |
| Color | : Colorless | |
| Application Temperature | : +41°F to +95°F (+5°C to +35°C) | |
| Density | : 8.85 ± 0.08 lb/gal | ASTM D1875 |
| Flashpoint | : >177.8°F (>81°C) | |
| Viscosity | : 1200 - 1800 Cps at 77°F (25°C) | ASTM D1084 |
| Temperature Resistance | : +77°F to +158°C (-20°C to +70°C) | |

Activator

| | |
|-------------------------|------------------------------------|
| Activator Basis | : Hexane |
| Appearance | : Aerosol |
| Color | : Colorless |
| Application Temperature | : +41°F to +95°F (+5°C to +35°C) |
| Temperature Resistance | : +77°F to +158°C (-20°C to +70°C) |

Packaging

| Product Type | Volume / Weight | Packaging |
|------------------|---|-----------|
| Activator & Glue | 6.75 Fl Oz. + 1.75 Oz (200 mL + Net Wt. 50 gr) | 48 |
| Activator & Glue | 13.5 Fl Oz. + 3.5 Oz (400 mL + Net Wt. 100 gr) | 24 |