

SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135

Conv

Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

SECTION 1. IDENTIFICATION

Product name : ALEXSEAL C1357-Cor Spec Primer 135 Conv farblos / transparent

Product code : 1558000000000

Manufacturer or supplier's details

Manufacturer, importer, supplier : Mankiewicz Coatings L.L.C

Address : 1200 Charleston Regional Parkway
Charleston, South Carolina 29492
USA

Telephone : +1 (843) 6547755

Telefax : +1 (843) 6547759

E-mail address : sdb_info@umco.de

Emergency telephone : USA Toll free +1 866 928 0789 EN/FR/ES(Carechem International)
Canada Toll free +1 800 579 7421 EN/FR (Carechem International)

Recommended use of the chemical and restrictions on use

Recommended use : Industrial serial painting

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1



SAFETY DATA SHEET

Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)
- single exposure

Specific target organ toxicity : Category 2
- repeated exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H312 + H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135

Conv

Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Hardener based on polyamine / amino adduct

Components

Chemical name	CAS-No.	Concentration (% w/w)
xylenes (Technical mixture)	1330-20-7	>= 40 - <= 100
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	>= 25 - < 40
butan-1-ol	71-36-3	>= 20 - < 25

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 155800000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.
- Most important symptoms and effects, both acute and delayed : Harmful in contact with skin or if inhaled.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!
- Special protective equipment for fire-fighters : As in any fire, wear self-contained breathing apparatus pressure - demand, MSHA / NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Exclude sources of ignition and ventilate the area.
Do not inhale vapors.
Refer to protective measures listed in sections 7 and 8.



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

- Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.
- Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).
Clean preferably with a detergent; avoid use of solvents.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
Preparation may charge electrostatically: always use earthing leads when transferring from one container to another.
Operators should wear anti-static footwear and clothing. No sparking tools should be used.
Vapors are heavier than air and may spread along floors.
Vapors may form explosive mixtures with air.
- Advice on safe handling : Avoid contact with the skin and the eyes.
Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentrations higher than the occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type.
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.
Keep container dry in a cool, well-ventilated place.
- Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.
- Recommended storage temperature : 41 - 95 °F / 5 - 35 °C



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
 Conv
 Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylenes (Technical mixture)	1330-20-7	VLE-PPT	100 ppm	NOM-010-STPS-2014
		VLE-CT	150 ppm	NOM-010-STPS-2014
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWA	100 ppm 434 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
		butan-1-ol	71-36-3	TWA
Further information: Eye irritation, Upper Respiratory Tract irritation				
		TWA	20 ppm 60 mg/m3	CA AB OEL
		TWA	15 ppm	CA BC OEL
		C	30 ppm	CA BC OEL
		C	50 ppm 152 mg/m3	CA QC OEL
		VLE-PPT	20 ppm	NOM-010-STPS-2014
		TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m3	NIOSH REL
		TWA	100 ppm 300 mg/m3	OSHA Z-1
		C	50 ppm	OSHA P0



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
 Conv
 Product No.: 1558000000000

Version 1.16	Revision Date: 10/07/2021	SDS Number: F-1558000000	Date of last issue: 09/24/2020 Date of first issue: 06/19/2015
-----------------	------------------------------	-----------------------------	---

		150 mg/m3
--	--	-----------

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
xylenes (Technical mix-ture)	1330-20-7	Methyl-hippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre-atinine	ACGIH BEI
		Methyl-hippuric acid	Urine	End of shift	1.5 g/g cre-atinine	MX BEI
		Methyl-hippuric acids	Urine	End of shift	1.5 g/g cre-atinine	CR BEI

Engineering measures : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapors concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use MSHA/NIOSH approved respirator if concentration exceeds recommended exposure levels.

Hand protection

Remarks : Glove permeation data does not exist for this material. The following glove(s) should be used for splash protection only:
 Appropriate material: nitrile

Eye protection : Use safety glasses or face shield (ANSI Z87.1 or approved equivalent).

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.

Protective measures : Do not eat or drink during work - no smoking.



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version 1.16	Revision Date: 10/07/2021	SDS Number: F-1558000000	Date of last issue: 09/24/2020 Date of first issue: 06/19/2015
-----------------	------------------------------	-----------------------------	---

Avoid product contact with skin, eyes and clothing.
Avoid the inhalation of dust from sanding, particulates and
spray mist arising from the application of this preparation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : according product name

Odor : characteristic

pH : 6 - 9 (68 °F / 20 °C)
Concentration: 10 g/l 10 %

Boiling point/boiling range : ca. 248 °F / 120 °C

Flash point : 77 °F / 25 °C
Method: ISO 13736

Upper explosion limit / Upper flammability limit : 9.4 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : ca. 100 hPa (122 °F / 50 °C)

Density : ca. 8 lb/gal (1 g/cm³)
(68 °F / 20 °C)

Solubility(ies)
Water solubility : insoluble

Autoignition temperature : 572 °F / 300 °C

Viscosity
Flow time : 59 s
Cross section: 4 mm
Method: DIN 53211
40 s



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135

Conv

Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

Cross section: 6 mm
Method: ISO 2431

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
- Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).
- Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.
- Hazardous decomposition products : When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful in contact with skin or if inhaled.

Product:

- Acute oral toxicity : Acute toxicity estimate: 2,624 mg/kg
Method: Calculation method
- Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.
- Acute toxicity estimate: 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: 2,000 mg/kg
Method: Calculation method

Components:

xylenes (Technical mixture):



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version 1.16	Revision Date: 10/07/2021	SDS Number: F-1558000000	Date of last issue: 09/24/2020 Date of first issue: 06/19/2015
-----------------	------------------------------	-----------------------------	---

Acute oral toxicity : LD50 Oral (Rat): 4,300 mg/kg

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version 1.16	Revision Date: 10/07/2021	SDS Number: F-1558000000	Date of last issue: 09/24/2020 Date of first issue: 06/19/2015
-----------------	------------------------------	-----------------------------	---

Remarks : Exposure of vapor concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Corrosive effect of product in contact with skin, eyes and mucous membranes. Risk of serious damage to eyes.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

tection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There are no data available on the preparation itself.
The product should not be allowed to enter drains or water courses.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : PAINT RELATED MATERIAL
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT RELATED MATERIAL

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1263
Proper shipping name : PAINT RELATED MATERIAL



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

Class : 3
Packing group : III
Labels : FLAMMABLE LIQUID
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Respiratory or skin sensitization
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylene (Technical mixture) 1330-20-7 >= 50 - < 70 %

butan-1-ol 71-36-3 >= 20 - < 30 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

xylene (Technical mixture) 1330-20-7 >= 50 - < 70 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

VOC content excluding water : 6 lb/gal (750 g/l)
For the calculation of VOC values in this section all substances have been considered which fall under the definition of VOC



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135

Conv

Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

according to 40 CFR 51.100. Additionally, the calculation complies with the requirements of SCAQMD Rule 1106.1, amended February 12, 1999.

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermedi-ate or Final VOC's (40 CFR 60.489):

xylenes (Technical mix- ture)	1330-20-7	>= 50 - < 70 %
butan-1-ol	71-36-3	>= 20 - < 30 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Ta-ble 116.4A:

xylenes (Technical mix- ture)	1330-20-7	>= 50 - < 70 %
----------------------------------	-----------	----------------

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

xylenes (Technical mix- ture)	1330-20-7	>= 50 - < 70 %
----------------------------------	-----------	----------------

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

xylenes (Technical mixture)	1330-20-7
butan-1-ol	71-36-3

Pennsylvania Right To Know

xylenes (Technical mixture)	1330-20-7
butan-1-ol	71-36-3

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California List of Hazardous Substances

xylenes (Technical mixture)	1330-20-7
butan-1-ol	71-36-3

California Permissible Exposure Limits for Chemical Contaminants

xylenes (Technical mixture)	1330-20-7
butan-1-ol	71-36-3

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory



SAFETY DATA SHEET


Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 1558000000000

Version 1.16	Revision Date: 10/07/2021	SDS Number: F-1558000000	Date of last issue: 09/24/2020 Date of first issue: 06/19/2015
-----------------	------------------------------	-----------------------------	---

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Health
0=Slightly Hazardous Slightly Hazardous
2=Hazardous
3=Extreme danger
4=Deadly

Flammability
0=Will not burn
2=Flashpoint below 200 F
3=Flashpoint below 100 F
4=Flashpoint below 73 F

Instability
0=Stable
1=Unstable if heated
2=Violent chemical reaction; water reactive
3=Shock or heat may detonate
4=May detonate

Special hazard
SA Simple Asphyxiant
ACID Acid
OX Oxidizer
W Water Reactive
CORR Corrosive

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135
Conv
Product No.: 155800000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
CR BEI	:	Maximum allowable occupational exposure limits in the workplace - Table 3. Adopted Biological Exposure Indices
CR OEL	:	Costa Rica. Maximum allowable occupational exposure limits in the workplace.
MX BEI	:	Official Mexican Norm NOM-047-SSA1-2011, Environmental Health - Biological exposure indices for workers occupationally exposed to chemical agents
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
NOM-010-STPS-2014	:	Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
CA QC OEL / C	:	Ceiling
CR OEL / TWA	:	Time weighted average 8-hr value
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
NOM-010-STPS-2014 / VLE-PPT	:	Time weighted average limit value
NOM-010-STPS-2014 / VLE-CT	:	Short term exposure limit value
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;



SAFETY DATA SHEET



Commercial Product Name: ALEXSEAL C1357-Cor Spec Primer 135

Conv

Product No.: 1558000000000

Version	Revision Date:	SDS Number:	Date of last issue: 09/24/2020
1.16	10/07/2021	F-1558000000	Date of first issue: 06/19/2015

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law.

Adhere to the national sanitary and occupational safety regulations when using this product.

This SDS have been created to comply with The Hazard Communication Standard (HCS)(29 CFR

1910.1200).

This SDS have been created to comply with the Hazardous Products Regulations(SOR/2015-17).

Revision Date : 10/07/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8

