

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

## SECTION 1. IDENTIFICATION

Product name : ALEXSEAL P2083-Fairing Compound 202Thick 9803 White  
Product code : 1541998033000

### Manufacturer or supplier's details

Manufacturer, importer, supplier : Mankiewicz Coatings L.L.C  
Address : 1200 Charleston Regional Parkway  
Charleston, South Carolina 29492  
USA  
Telephone : +1 (843) 6547755  
E-mail address : sdb\_info@umco.de  
Emergency telephone : USA Toll free +1 866 928 0789 EN/FR/ES(Carechem International)  
Canada Toll free +1 800 579 7421 EN/FR (Carechem International)

### Recommended use of the chemical and restrictions on use

Recommended use : Industrial serial painting

## SECTION 2. HAZARDS IDENTIFICATION

### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitization : Category 1

### GHS label elements



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**  
P261 Avoid breathing dust.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture of synthetic resins and pigments

### Components

Chemical name	CAS-No.	Concentration (% w/w)
4,4'-Isopropylidenediphenol, oligo-	25068-38-6	>= 25 - < 40



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

meric reaction products with 1-chloro-2,3-epoxypropane		
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	$\geq 12.5 - < 20$
1,6-bis(2,3-epoxypropoxy)hexane	16096-31-4	$\geq 5 - < 12.5$
Glass, oxide, chemicals	65997-17-3	$\geq 1 - < 5$
titanium dioxide	13463-67-7	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.  
Irregular breathing/no breathing: artificial respiration.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognised skin cleanser.  
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.  
If accidentally swallowed obtain immediate medical attention.  
Never give anything by mouth to an unconscious person.  
Keep at rest.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not combustible under normal conditions.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

- Specific hazards during fire fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Further information : DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!
- Special protective equipment for fire-fighters : As in any fire, wear self-contained breathing apparatus pressure - demand, MSHA / NIOSH (approved or equivalent) and full protective gear.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Take the precautions customary when handling chemicals. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not let product enter drains. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.
- Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Preparation may charge electrostatically: always use earthing leads when transferring from one container to another.
- Advice on safe handling : Avoid contact with the skin and the eyes. Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.
- Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

direct sunlight.  
Keep container dry in a cool, well-ventilated place.

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 41 - 95 °F / 5 - 35 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL

Engineering measures : Provide adequate ventilation. This should be achieved by the use of local exhaust ventilation and good general extraction.

### Personal protective equipment

Respiratory protection : None, but avoid breathing vapors if possible.

Hand protection

Remarks : Glove permeation data does not exist for this material.  
The following glove(s) should be used for splash protection



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

- only:  
Appropriate material: nitrile
- Eye protection : Use safety glasses or face shield (ANSI Z87.1 or approved equivalent).
- Skin and body protection : Clothing as usual in the chemical industry.  
Skin should be washed after contact.
- Protective measures : Do not eat or drink during work - no smoking.  
Avoid product contact with skin, eyes and clothing.  
Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : solid (68 - 77 °F / 20 - 25 °C, 1,013 hPa)
- Color : according product name
- Odor : characteristic
- pH : substance/mixture is non-soluble (in water)
- : No data available
- Boiling point/boiling range : ca. 212 °F / 100 °C
- Flash point : 214 °F / 101 °C  
Method: ISO 13736
- Vapor pressure : ca. 100 hPa (122 °F / 50 °C)
- Relative vapor density : No data available
- Density : ca. 9.35 lb/gal (1.12 g/cm<sup>3</sup>)



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

(68 °F / 20 °C)

Solubility(ies)  
Water solubility : insoluble

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : > 21 mm<sup>2</sup>/s

Flow time : > 150 s  
Cross section: 4 mm  
Method: DIN 53211

> 100 s  
Cross section: 6 mm  
Method: ISO 2431

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).

Incompatible materials : Keep away from oxidizing agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.

Hazardous decomposition products : No hazardous decomposition products known.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified due to lack of data.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

## Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye irritation.

## Respiratory or skin sensitization

### Skin sensitization

May cause an allergic skin reaction.

### Respiratory sensitization

Not classified due to lack of data.

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

<b>IARC</b>	Group 2A: Probably carcinogenic to humans Glass, oxide, chemicals (glass)	65997-17-3
	Group 2B: Possibly carcinogenic to humans Glass, oxide, chemicals (special-purpose fibres)	65997-17-3
	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## Reproductive toxicity

Not classified due to lack of data.

## STOT-single exposure

Not classified due to lack of data.

## STOT-repeated exposure

Not classified due to lack of data.

## Aspiration toxicity

Not classified due to lack of data.





# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

## Further information

### Product:

Remarks : The liquid splashed in the eyes may cause irritation and reversible damage.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

#### Components:

#### **4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane:**

Toxicity to fish : LC50 (Fish): 1.3 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia): 2.1 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

### Persistence and degradability

#### Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

### Mobility in soil

#### Product:

Mobility : Remarks: There are no data available on the preparation itself.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

self.

## Other adverse effects

### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There are no data available on the preparation itself.  
The product should not be allowed to enter drains or water courses.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

UN/ID No. : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700), REACTION PRODUCT:BISPHENOL-F-(EPICHLORHYDRIN), EPOXY RESIN)

Class : 9  
Packing group : III  
Labels : Miscellaneous Dangerous Goods  
Packing instruction (cargo) : 956



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

aircraft)  
Packing instruction (passenger aircraft) : 956  
Environmentally hazardous : yes

### IMDG-Code

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700), REACTION PRODUCT:BISPHENOL-F-(EPICHLORHYDRIN), EPOXY RESIN)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700), REACTION PRODUCT:BISPHENOL-F-(EPICHLORHYDRIN), EPOXY RESIN)  
Class : 9  
Packing group : III  
Labels : CLASS 9  
Marine pollutant : yes(reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700), REACTION PRODUCT:BISPHENOL-F-(EPICHLORHYDRIN), EPOXY RESIN)  
Remarks : Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

### Special precautions for user

Remarks : 49CFR: no dangerous good in non-bulk packaging



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Acute Health Hazard  
Respiratory or skin sensitization  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

VOC content excluding water : 0.01 lb/gal (0.6 g/l)  
For the calculation of VOC values in this section all substances have been considered which fall under the definition of VOC according to 40 CFR 51.100. Additionally, the calculation complies with the requirements of SCAQMD Rule 1106.1, amended February 12, 1999.

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

## US State Regulations

### Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

### Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

### Pennsylvania Right To Know

aluminium oxide (Smoke) 1344-28-1

### Maine Chemicals of High Concern

octamethylcyclotetrasiloxane 556-67-2

### Vermont Chemicals of High Concern

octamethylcyclotetrasiloxane 556-67-2

### Washington Chemicals of High Concern

Product does not contain any listed chemicals

### California Prop. 65

WARNING: This product can expose you to chemicals including Glass, oxide, chemicals, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Permissible Exposure Limits for Chemical Contaminants

titanium dioxide 13463-67-7

### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

## SECTION 16. OTHER INFORMATION

### Further information



# SAFETY DATA SHEET


according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

## NFPA 704:



## HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Health  
0=Slightly Hazardous  
2=Hazardous  
3=Extreme danger  
4=Deadly

Flammability  
0=Will not burn  
2=Flashpoint below 200 F  
3=Flashpoint below 100 F  
4=Flashpoint below 73 F

Instability  
0=Stable  
1=Unstable if heated  
2=Violent chemical reaction; water reactive  
3=Shock or heat may detonate  
4=May detonate

Special hazard  
SA Simple Asphyxiant  
ACID Acid  
OX Oxidizer  
W Water Reactive  
CORR Corrosive

### Full text of other abbreviations

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

- CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- CA AB OEL / TWA : 8-hour Occupational exposure limit
- CA BC OEL / TWA : 8-hour time weighted average
- CA QC OEL / TWA EV : Time-weighted average exposure value
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AIRC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Commercial Product Name: ALEXSEAL P2083-Fairing Compound  
202Thick  
Product No.: 1541998033000

Version	Revision Date:	SDS Number:	Date of last issue: 07/31/2023
1.22	12/27/2023	F-1541998033	Date of first issue: 05/28/2015

The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law.

Adhere to the national sanitary and occupational safety regulations when using this product.

This SDS have been created to comply with The Hazard Communication Standard (HCS)(29 CFR

1910.1200).

This SDS have been created to comply with the Hazardous Products Regulations(SOR/2015-17).

Revision Date : 12/27/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8

