

KABLE KONTROL

Adhesive Cable Tie Mounts 6:6

Description:

Adhesive-backed nylon zip tie mounts are designed to be used together with cable ties. Adhesive zip tie mounts are an easy solution to secure your wire bundles or other items to any surface you desire. Adhesive-backed cable tie mount can be secured to the surface by the adhesive tape on the back after the backing paper is peeled off. May be secured using a self-tapping screw inserted into a special hole.



Available in both black and natural. For use with 18 lb - 50 lb tensile strength cable ties. Custom configurations upon request.


ADHESIVE BACKED CABLE MOUNTS



Applications:

Adhesive cable tie mounts are ideal for wide variety of applications such as:

- Electrical Installations
- Cable management
- Attached cables to a fixed surface
- Securing Bundles in limited spaces
- Routing cables where holes cannot be drilled
- Outdoor Installations with black adhesive mounts
- Packaging

|  | Item # | A (Inches) | B (Inches) | C (Inches) | D (Inches) | H (Inches) | Case Quantity |
|---|---------------|------------|------------|------------|------------|------------|---------------|
| | CT280/CT280-B | 1.06 | 0.2 | 1.06 | 0.2 | 0.2 | 55 |
| | CT281 | 0.5 | 0.126 | 0.5 | - | 0.126 | 500 |
| | CT282 | 0.5 | 0.126 | 0.5 | - | 0.126 | 500 |
| | CT283/CT284 | 0.75 | 0.177 | 0.75 | 0.126 | 0.154 | 200 |
| | CT285/CT286 | 1.5 | 0.394 | 1.5 | 0.197 | 0.2295 | 40 |



| MATERIAL | MIN OPERATING TEMPERATURE | MAX OPERATING TEMPERATURE | UV RESISTANCE | UL FLAME RATING |
|-----------------------------------|---------------------------|---------------------------|---------------|-----------------|
| Nylon 6/6- Natural | -40°F -40°C | 185°F 85°C | None | 94V-2 |
| Nylon 6/6- UV Stabilized Black | -40°F -40°C | 185°F 85°C | Very High | 94V-2 |