



OK

F4640009 - White

Designed by Konstantin Grcic

Lamp providing direct light. Head in gloss varnished or chromed die-cast aluminium. Body in injection-stamped PA66+30%FV with cover in gloss varnished or chromed die-cast aluminium. Orientable head. The light fitting can be moved vertically by running the internal structure of the body on a steel cable tensioned between the ceiling and the floor (useful length 4000mm). Dimmable switch with Soft Touch technology. Adaptor on plug connector with interchangeable plugs.

Main specifications


Mounting Lamp holder LED Module Suspension **Environment** Indoor dry Autoprotected Lamp Νo location Number of heads Light source type LED Source Power (W) 18 System Flux (lm) 1551 Light source replaceable ${\sf Replaceable}$ (LED only) light

source by a professional LED Module

LED type

Optical

Lighting TypeDirectLighting distributionSymmetricCCT (K)2700KCold Beam LightingNoExtreme Cut offNo



Electrical

Dimmable type

included Electronic 12V Batteries Inside Power supply replaceable

Cord length (mm) Plug Type

Charging Min Time

No Replaceable control gear by an end-user 4000 Type G, Type A, Type C

Physical

Colour White
Net weight (kg) 2.9
Gross weight (kg) 6.39
IP 20
IP external 20