

manufacturer:**SaverSystems**

Richmond, IN 47374

800-860-6327

Fax: 765-935-4999

www.defywoodstain.com

DESCRIPTION

DEFY Composite Deck Cleaner cleans and restores the natural beauty of exterior composite wood. This product is also an excellent cleaner for vinyl, ALUMINUM, fiberglass, and concrete surfaces.

Uses

DEFY Composite Deck Cleaner removes dirt, grime, black stains, previous coatings (not paint) and weathered graying from horizontal and vertical composite wood surfaces. It is recommended for surface preparation prior to application or reapplication of clear finishes and stains (for best results use DEFY Extreme Composite Deck Sealer).

ADVANTAGES

- Removes graying/black stains
- Contains no acid or chlorine bleach
- Safe for most plants and vegetation
- Great "Whole House" cleaner
- Ideal for composite decking

DIRECTIONS FOR USE: Use 6 oz. (3/4 cup) of DEFY Composite Deck Cleaner with each gallon of water. One gallon of solution cleans 100-200 sq. ft. depending on wood porosity.

STEP 1: MIX: Mix with water and stir thoroughly until powder is dissolved. Powder dissolves faster in warm water. Solution should be used within six hours of mixing.

STEP 2: APPLY: Horizontal Surfaces – Dampen surface with water before application. Apply DEFY Composite Deck Cleaner solution with a pump sprayer, brush, or mop, working on small areas (20-30 sq. ft.) at a time. Vertical Surfaces – Dampen surface with water before application. Apply with a pump sprayer working on small areas at a time. Start at the bottom and work to the top.

STEP 3: BRUSH: Horizontal Surfaces – Let solution stand approximately 10-20 minutes, keeping area wet with additional DEFY

Composite Deck Cleaner solution. Thoroughly scrub with a stiff, short bristle broom or brush. Vertical Surfaces – Let stand approximately 10-20 minutes, keeping surfaces wet with additional solution. Thoroughly scrub with brush, working from bottom to top. DEFY Composite Deck Cleaner will open wood pores and some raising of wood fibers may occur.

STEP 4: RINSE: Rinse thoroughly with water from garden hose or power washer (with 800-1200 psi) using lowest pressure that cleans without damaging the surface. Repeat steps 2-4 on next small area. Continually rinse cleaned area of vertical surfaces to avoid streaking as work progresses. Allow composite wood surfaces to thoroughly dry before applying DEFY Extreme Composite Deck Sealer. Heavily weathered or soiled surfaces may require a second application.

Safety and Handling: Solution will not harm grass, plants and marine life. Rinse grass and plants thoroughly with water after exposure. Contact with combustible organic materials may cause fire. Accumulation of product on ladders, scaffolding, docks etc., may result in slippery surface.

Coverage: Each gallon of diluted cleaner cleans and restores 100-200 sq. ft. depending on wood porosity.

Clean Up

Clean tools and equipment immediately after each use with soap and water.

Precautions

DANGER! Corrosive. Causes eye & skin burns. Harmful or fatal if swallowed. Oxidizer - contact with flammable or combustible material may cause fire. **Keep out of reach of children.** Do not take internally. Avoid contact with eyes and mucous membranes and prolonged contact with skin. Eye protection, gloves, and protective clothing are recommended when using this product. Avoid breathing mist. Close container tightly after each use. Do not re-use containers. Contains sodium carbonate peroxyhydrate, tetrasodium pyrophosphate, and sodium metasilicate. Do not mix with chlorine bleach or other chemicals. Store in original container only.

First Aid

If inhaled: Move to fresh air. If swallowed: Rinse mouth. Do NOT induce vomiting. Never give an unconscious person anything to drink. Immediately call a POISON CENTER or doctor/physician. Oxygen and/or artificial respiration may be necessary. **For skin contact:** Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Get medical attention if irritation persists. **For eye contact:** Immediately flush eyes thoroughly with water for at least 15 minutes, including under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately. For additional information for this product, consult the Safety Data Sheet available at defywoodstain.com.

Limited Warranty

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

Packaging

Available in 2 lb. recyclable plastic containers.

Transport And HANDLING

Do not stack pallets. Store in cool, dry area.

Physical Properties

COLOR..... White
ODOR..... Slight chemical odor
SHELF LIFE..... 36 months when unopened