Metlam Australia Pty Ltd 1300 METLAM sales@metlam.com.au www.metlam.com.au

SHOWER SEATS & SHOWER RELATED




ML_SK1078_SS

Universal Sliding Shower Rail Kit

Specification

#304 Stainless Steel grab rail, chrome/grey hand shower, chrome 2.0m high pressure hose, Chrome Elbow and Grab Slider.
Satin Stainless Steel
Concealed Fix - 78mmØ Mount, universal mounting for left or right handed installation.
Grab Rail 1100mm X 700mm, 32mm Shower Kit.
Shower heads have MAXIMUM flow rate of 8 litres per minute, kits have watermark WMKT21090, hoses are standard pressure of 150-350Kpa as per AS/NZS 3662.2006 WELS: 3 Star - 8.5 L/min
* This unit is accessible compliant when installed in accordance with AS1428.1 guidelines. * It is the responsibility of the installer to ensure that the surface/substrate that the unit is installed upon and the fixings used are suitable to withstand the weight bearing loads of the unit and if required as per AS1428 / Australian building code regulations. * Compliant with the Force Requirements within AS1428.1: 2021, Section 14.





Downloads & Resources

Care & Maintenance Installation instructions Associated Videos Stainless Steel Cleaning & Maintenance

The photographs and line drawings of the products presented above are representational only.

Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.