

8825-12: One Light Outdoor Wall Lantern



Collection: Brentwood

Black Powdercoat Cast Aluminum Single Light Outdoor Wall Lantern with Clear Glass. Angular Shaping.

Rugged but decorative cast aluminum. Outdoor wall lantern made with durable black powdercoat finish over cast aluminum and clear glass.

UPC #:785652882524

Finish: Black (12)

Dimensions:

Width: 10 1/4" Extends: 10 3/4" Height: 18" Wire: 6 1/2"

Mounting Proc.: Center Lock-Up

Connection: Mounted To Box

Bulb Appearance: Clear

Bulbs:

1 - Medium A19 100w Max. 120v - Not included1 - LED Medium A19 8w Max. 120v - Not included1 - LED Medium A19 13.5w Max. 120v - Not included

Features:

- Clear bulb(s) recommended for this fixture
- Easily converts to LED with optional replacement lamps
- · Powdercoat finish included long finish life

Material List:

1 Canopy - Die Cast Aluminum - Black1 Cap - Die Cast Aluminum - Black1 Body - Die Cast Aluminum - Black

Safety Listing:

UL Listed for Wet Locations cUL Listed for Wet Locations

Instruction Sheets:

English (HC-329)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Panel	Glass	Clear	6			3 5/8	7 11/16					

Backplate / Canopy Details:

Туре	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Back Plate	6 7/16	4 1/4	3/4		4 3/4	13 1/4

Replacement Bulb Data:

Product #		Туре	Base	Watts	Watts Consumed	Volts	Hours	Lumens	Temp (°K)	CRI
97308S	Frosted	A19	E-26 Medium	8	8	120v	50000	450	3000	85
97408S	Frosted	A19	E-26 Medium	8	8	120v	50000	450	2700	85
97309S	Frosted	A19	E-26 Medium	13.5	13.5	120v	50000	800	3000	85
97409S	Frosted	A19	E-26 Medium	13.5	13.5	120v	50000	800	2700	85

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	8825-12	1	785652882524	13.25	11.75	12.25	1.104	7.26	125	Yes
NJ Pallet		54		48	40	68	75.556	378		No

Vist our web site at www.SeaGullLighting.com 8825-12 - page 2 of 2

NV Pallet	54	l i	48	40	68	75.556	378	No