Zire Semi-Flush Mount Convertible Chandelier

3190303 1.0

GENERATION LIGHTING

CHANDELIER

CAUTION - RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°c supply conductors.

GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.

Incandescent version may be dimmed with a standard incandescent dimmer. LED version may be dimmed with a LED dimmer. Consult lamp manufacturer for additional information.

This instruction shows a typical installation.


GENERATION LIGHTING


7400 Linder Ave, Skokie, IL 160077 800.969.3347

www.generationlighting.com


© 2019 Generation Lighting. All rights reserved.

The "Generation Lighting" graphic is a registered trademark of Generation Lighting. Generation Lighting reserves the right to change specifications for product improvements without notification.





Install the Fixture



- This fixture can be installed as a chain hung chandelier or semi-flush mount chandelier. Determine the desired fixture appearance and follow the appropriate steps for your installation.
- 2 Secure the mounting plate to the junction box.
- Chain Installation Only: Insert the threaded pipe into the pipe cover, then feed fixture wires through the pipe and screw it onto the top of the fixture.
- 4 Chain Installation Only: Feed the fixture wires through the fixture loop and screw it onto the threaded pipe.
- Chain Installation Only: Determine the wanted height of the fixture and remove a portion of the chain from the bottom by opening a link with pliers.
- 6 Chain Installation Only: Open the chain link with pliers and install the chain on the fixture loop, then re-close the chain link.
- **Chain Installation Only:** Open a link on the other end of the chain with pliers and install the chain onto the canopy loop to secure the fixture, re-close the link with pliers.
- Chain Installation Only: Weave the cord through the chain, canopy loop, canopy, and out of the junction box. Trim the cord leaving enough to make electrical connections. Skip to step 12
- 9 Semi-Flush Installation Only: Feed the fixture wires through the threaded pipe and screw it onto the top of the fixture.
- Semi-Flush Installation Only: Feed the fixture wires through the pipe cover and decorative washer, then slide them over the threaded pipe.
- Semi-Flush Installation Only: Place the canopy onto the threaded pipe and secure them together using the lock washer and hex nut.
- Connect the fixture to a suitable ground in accordance to local electrical codes.
- Connect the white fixture wire (square and/or rigid) to the neutral power line wire with a wire nut.
- Connect the black fixture wire (round and/or smooth) to the hot power line wire with a wire nut.
- Neatly place all the wires into the junction box, place the canopy onto the mounting studs, and secure it in place by screwing the cap nuts onto the studs.
- Install the candle tubes by sliding them over the sockets.
- Screw the lamps into the sockets. Refer to the label on the socket for Max Wattage Information.
- Place the shade over the socket and into the shade base ensuring that it is secured by the spring clips inside the base. Repeat for remaining shades.
- Install the cup to the bottom of the fixture and secure it in place using the finial.