
### **ASSEMBLY INSTRUCTIONS**



## Bryant Grande Chandelier

Item # TOB 5196

#### **NOTICE:**

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

### **TOOLS REQUIRED (NOT INCLUDED):**

Phillips Screwdriver Slotted Screwdriver Wire Cutters

Slip Joint Pliers Wire Strippers

- 1. Carefully remove all parts from the box. Place on a clean, soft surface.
- 2. Remove mounting plate **(B)** from canopy **(E)** by removing canopy screws (D).
- 3. Install mounting plate (B) to junction box and secure with mounting screws (C).
- 4. Thread rod (I) to fixture body (J).
- 5. Feed fixture wires through rod (H) and connect to rod (I). Repeat for rod (G), connecting to rod (H).
- 6. Continue feeding fixture wires through top rod (F) and canopy (E).
- Thread canopy (E) to rod (F).
- Cut excess wires, being sure to leave enough to reach the junction box. Separate wires, and strip insulation on each 5/8".
- 9. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut (A).

**NOTE:** It is imperative that the fixture is grounded.

- 10. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut (A).
- 11. Connect fixture hot wire (black) to the supply hot wire (usually black) using wire nut (A).

**CAUTION:** Do not reverse the hot and neutral connections.












## **ASSEMBLY INSTRUCTIONS**



# Bryant Grande Chandelier

Item # TOB 5196

### **NOTICE:**

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

- 12. Make sure all wire connections are tight, then carefully tuck into the junction box.
- 13. Install canopy **(E)** to mounting plate **(B)** and secure with canopy screws **(D)**.
- 14. Thread rod (K) to the bottom of fixture body (J).
- 15. Install light bulbs into sockets.
- 16. Clip shades (L) onto light bulbs.
  NOTE: If shade has additional packaging, carefully cut off from interior of shade to avoid damages.

**Care Instructions:** Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.







