

SEMI RIGID ALUMINIUM DUCTING HOSE

SKU / PART NUMBER: FAD

Application: Heating & Cooling Systems

Bend Radius: 0.76 x D

Temperature Rated: -30°C to +150°C

Standard: BS476 Parts 6 & 7 Class 0



Semi-Rigid Aluminium Ducting is a perfect compromise between the strength of galvanised rigid duct and the versatility of aluminium flexible duct. Supplied in a compressed 4 Metre length and can be used with extractor fans, heating/cooling systems, portable air conditioners, cooker hoods, tumble dryers, and ventilation systems. Versatile and durable aluminium hose with no reinforcement.

Can be twisted and bent around obstacles, but is stronger than typical aluminium flexible hose. Capable of handling higher working temperatures than other ducts and so is suited for boiler or heating applications.

Internal Diameter	Outside Diameter	Rating	Number of Layers	Bend Radius	Maximum Length
76mm	84mm	BS476	1	0.76 x D	4 Metres
102mm	110mm	BS476	1	0.76 x D	4 Metres
125mm	133mm	BS476	1	0.76 x D	4 Metres
150mm	158mm	BS476	1	0.76 x D	4 Metres

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)