

LAYFLAT DISCHARGE WATER HOSE

SKU / PART NUMBER: LFH

Application: Drainage, Water Supply & Irrigation

Reinforcement: Polyester

Temperature Rated: -15°C to +55°C

Working Pressure: 4 Bar / 60 PSI

Colour: Blue / Yellow



Layflat hose is a light weight flexible PVC lay flat hose, for delivery of liquids under pressure. Suitable for a range of applications such as drainage, water supply, irrigation and sprinkler systems. This can also be used for chemical transfer such as liquid fertilisers and other agricultural chemicals. Our PVC Lay flat hoses with polyester reinforcement are very flexible and resistant to kinks allowing for easy transportation when not in use.

Lay Flat discharge hose is only suitable for open ended discharge applications and the pressure ratings are based on discharge pressure from the pump unit. It is worth noting that any substantial increase in temperature above 20oC can result in a decline in working operational pressure values.

SKU	Internal Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Maximum Length
LFH025	25mm	29mm	2mm	4 Bar	12 Bar	100 Metres
LFH032	32mm	36mm	2mm	4 Bar	12 Bar	100 Metres
LFH038	38mm	42mm	2mm	4 Bar	12 Bar	100 Metres
LFH051	51mm	55mm	2mm	4 Bar	12 Bar	100 Metres
LFH063	63mm	67mm	2mm	4 Bar	12 Bar	100 Metres
LFH076	76mm	80mm	2mm	4 Bar	12 Bar	100 Metres
LFH102	102mm	106mm	2mm	4 Bar	12 Bar	100 Metres

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)

Unit 3 Holmebank Mills, Station Road, Mirfield, West Yorkshire, WF14 8NA - [Find us on Google Maps](#)
AP Motor Store Limited - VAT No. GB334646006 - Reg No. 09188175