

PVC CORRUGATED FLEXIBLE DUCT HOSE

SKU / PART NUMBER: PDH

Application: Liquid, Air & Powders

Reinforcement: Rigid PVC Helix

Temperature Rated: -10°C to +55°C

Features: Highly Flexible & Small Bending Radius

Cover: Black Corrugated PVC



Lightweight PVC hose with a rigid crush resistant white PVC helix. Tough, flexible and extremely durable under normal operating conditions. The cross section is maintained even when highly flexed.

Minimum frictional loss is achieved by the smooth bore. The corrugation in the hose gives it strength and flexibility, allowing you to turn tight corners without it kinking.

Quality PVC reinforced with an integral helix of rigid PVC, corrugated outer surface provides high flexibility and small bending radius. Smooth inner surface ensures it is excellent for the conveyance of liquid, air & powders. High abrasion resistant.

Inside Diameter	Outside Diameter	Working Pressure	Bursting Pressure	Maximum Coil
19mm	23mm	6 Bar	18 Bar	30 Metres
25mm	30mm	6 Bar	18 Bar	30 Metres
32mm	38mm	6 Bar	18 Bar	30 Metres
38mm	44mm	6 Bar	18 Bar	30 Metres
50mm	58mm	5 Bar	15 Bar	30 Metres

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)