

PVC WIRE REINFORCED SUCTION & DELIVERY HOSE

SKU / PART NUMBER: WPH

Application: Suction & Delivery of Water / Chemicals

Reinforcement: Steel Wire Helix

Temperature Rated: -20°C to +65°C

Standard: BS6066 / ISO5774



Wire reinforced PVC Hose is suitable for a range of applications including delivery of food, water chemicals or other waste materials. Constructed from clear PVC with a high tensile steel helix and is water resistant, durable, smooth bore, good abrasion, rot and chemical resistance, good crush and kink resistance. Preferable for the suction and delivery of water, slurries and dilute chemicals.

Inside Diameter	Outside Diameter	Working Pressure	Bending Radius	Maximum Coil
10mm	16mm	12 Bar	2 x Diameter	30 Metres
13mm	19mm	10 Bar	2 x Diameter	30 Metres
16mm	22mm	10 Bar	2 x Diameter	30 Metres
19mm	26mm	9 Bar	2 x Diameter	30 Metres
25mm	33mm	8 Bar	2 x Diameter	30 Metres
32mm	42mm	7 Bar	2.5 x Diameter	30 Metres
38mm	49mm	7 Bar	2.5 x Diameter	30 Metres
51mm	65 Bar	6 Bar	2.5 x Diameter	30 Metres
63mm	77Bar	4 Bar	2.5 x Diameter	30 Metres

Tel : 01924 496111

Web: autosiliconehoses.com

Email: web@autosiliconehoses.com

Google: [Find us on Google](#)

Unit 3 Holmebank Mills, Station Road, Mirfield, West Yorkshire, WF14 8NA - [Find us on Google Maps](#)
AP Motor Store Limited - VAT No. GB334646006 - Reg No. 09188175