

BRIGHTO WALL EMULSION

General Description	Brighto Wall Emulsion is an economical interior emulsion with a smooth and slight glossy finish. It is suitable for all normal interior masonry surfaces including brickwork, Plaster, cement and wallboards etc.	
Pack Size	3.64 Litres, 14.56 Litres	
Colour Range	See Brighto Wall Emulsion shade card	
Film Properties Water Resistance	Will tolerate the levels of atmospheric humidity present in normal environment.	
Composition (Nominal)	Pigment: Lightfast Pigments Binder: PVA Copolymer Solvent: Water	
Volume Solids	White 42 ± 2% (nominal), other colors will vary	
Density	1.60 ± 0.03; Theoretical for white only	
Non-volatile Matter Content	64 ± 2; Theoretical	
VOC Contents	0.08 g / L; ASTM D 3960	
Film Thickness/Coat	Wet: 75 - 100 Micrometers Dry: 31 - 42 Micrometers	
Drying Times	Depends on temperature, humidity, air movements and film thickness	
Touch Dry	2 - 3 Hours	
Recoat	4 - 6 Hours	
Hard Dry	72 Hours	
Theoretical Coverage	A guide to the theoretical coverage which can be achieved under normal conditions is 10 - 14 m ² /liter /coat.	
Application	Brush, Roller, Spray	
Thinner	Water	
Thinning Brush or Roller Conventional Spray	10 - 25% 30 - 40%	
Cleaning Up	Clean all equipment with clean water immediately after use.	

Surface Preparation	New, bare, old or previously painted surfaces must be clean, dry and free from dust or wax. Clean the surface by rubbing down the abrasive paper. Brush down previously painted surface completely and make the surface smooth. For large holes and cracks, use plaster of paris or white cement. Allow to dry. Apply Brighto Wall Primer in order to seal the surface from water and salts. Allow surface to dry completely. Then apply Brighto Wall Putty and allow to dry. Rub down the surface with abrasive paper and dust off. Now the surface will be smooth and ready for Brighto Wall Emulsion to be applied. Stir the paint thoroughly before use.	
---------------------	---	--

Recommended Paint System	Brighto Wall Primer	1 Coat
	Brighto Wall Putty	2 Coats
	Brighto Wall Emulsion	2 - 3 Coats

Flash Point	31.5°C
-------------	--------

Safety, Health and Environmental Information	Keep container tightly closed and upright to prevent leakage when not in use. Don't breathe in vapors and sanding dust. Cartridge mask should be worn when rubbing down. Provide adequate ventilation during application and drying. If you experience difficulty in breathing, move to fresh air. Don't permit smoking in the vicinity. Avoid contacts with eyes and skin. Wear gloves and goggles during application or sanding. In case of contact with eyes, flush with plenty of water and seek medical advice. To remove splashes from skin, use soap and water or recognized skin cleaner. Protect from extremes of temperatures. Store in a cool dry place but also protect from freezing. In case of fire, use foam, dry powder, CO2 fire extinguisher. Keep away from source of ignition. Close container tightly after each use. Keep out of reach of children. In case of accident, collect spillage using sand or clay and dispose of paint waste in accordance with appropriate environmental quality requirements.	
--	---	--

Any advice recommendations, information, assistance or service provided by Brighto Paints Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.