



Cable gland, Thread type: metric, Thread size: 40 mm, Material: Brass, Protection: IP 69K / IP 68 - 5 bar, Colour: natural

Business data

| | |
|--|------------------|
| Article number | <u>17775.2</u> |
| Article name | KV/M-L 40x1,5-MS |
| GTIN (EAN) | 4044211154042 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 208 g |
| Weight per piece (including packaging) | 208 g |
| Unit of weight | G |
| Customs number | 74199990 |
| Country of origin | EU |
| Product description | Cable gland |
| Colour | Natural |

Technical data

Dimensions

| | |
|-----------------------------------|-------|
| Width (enclosure size) | 51 mm |
| Min. height (enclosure size) (TL) | 51 mm |
| Depth (enclosure size) | 51 mm |

Thread

| | |
|-------------------|--------|
| Thread type | Metric |
| Thread size | 40 mm |
| Thread pitch | 1.5 mm |
| Thread length (L) | 15 mm |

Materials

| | |
|---------------------------|-----------|
| Material | Brass |
| Surface | Nickel |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 100 °C |
| Sealing material | EPDM |
| Type of seal | Seal ring |
| Halogen-free | ✓ |


Further technical data

| | |
|-----------------------------|----------------------|
| Degree of protection | IP69K / IP68 - 5 bar |
| Spanner width (AF) | 46 mm |
| Strain relief | ✓ |
| Cable diameter, min. | 16 mm |
| Cable diameter, max. | 28 mm |
| Impact resistant | ✓ |
| Hexagonal corner size | 51 mm |
| Impact category | 6 |
| Installation torque cap nut | 20 Nm |
| Installation torque fitting | 20 Nm |
| Type of cable anchorage | A |

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Media



Accessories
