角 Uni-Dose

Uni-Dose® Series UD Chemical Metering Pump

Universal Solution

Introducing the universal Uni-Dose® Series UD chemical metering pump, engineered to address common well water treatment requirements. This single model does it all at an affordable price. Its simplified design makes it easier than ever to install, maintain, and operate. Water treatment accuracy has never been easier!

Versatile & Flexible

A single speed control knob provides easy, accurate adjustment over the entire operating range. Precise capacity control from 1 to 24 gallons per day (4 to 90 LPD) at 80 psi (5.5 bar), with speeds up to 160 SPM. A full range of performance, delivered by a single pump model.

Quiet & Convenient

The advanced noise reduction design makes the UD pump ideal for residential water conditioning applications. The new integrated FastPrime™ priming valve allows for fast and easy start-up.

Durable & Reliable

Totally enclosed NEMA 4X/ IP65 housing provides superior protection in either indoor or outdoor installations with UV and heat resistance to 122°F (50°C). A universal 115-230V, 50/60Hz power supply with internal varistor and fuse protect the unit from power surge damage. Uni-Dose® is built to last.

Performance Specifications

Technical Data

| Output Range | 1-24 GPD (0.16-3.8 LPH) |
|-----------------------|------------------------------|
| Pressure Range | 80 PSI (5.5 Bar) |
| Flow Rate Control | Variable speed, Fixed stroke |
| Min Stroke | 1 SPM |
| Max Stroke | 160 SPM . |
| Electric Supply | 115-230V, 50/60 Hz |
| Max Current @ 120 VAC | 0.3 amps |
| Installation | Indoor/Outdoor |
| NEMA/IP Rating | NEMA 4X/IP65 |
| Certifications | NSF 61, UL |
| Suction/Discharge | Single cartridge check valve |

Output Information

| Model | Gallons per Day | | Gallor Ho | ns per our | 6 153000000000 | rs per lay | Liters per Hour | | 20032778111533 | c per in |
|-------|--------------------|------|--------------|---------------|----------------|---------------|--------------------|------|----------------|-------------|
| UD | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| עט | 1.0 | 24.0 | 0.04 | 1.0 | 3.79 | 90.85 | 0.16 | 3.80 | 2.70 | 63.0 |

Configuration Data Model UD001-238NU

| UD00 | Uni-Dose Series |
|------|--|
| 1* | 115-230V 50/60HZ, USA 120V Plug |
| 238 | PVC Head & fittings with PTFE LIQUIFRAM™ |
| NU | UV resistant inch tubing |

^{* 220-240}V USA Plug available upon request

