



TRIREX

Mobile Fall Protection



www.leadingedgesafety.net
(888) 990.2990

TR-000-01-20 with 10ft³ and 20ft³ Job Boxes

Product Information

Fall Arrest Capacity	Three Workers
Fall Restraint Capacity	Two Workers (Maximum Fall Arrest & Restraint capacities may be used simultaneously.)
Net Weight	1220 LBS
Tires	8.5" x 18" Solid Polyurethane 15 in ² calculable surface area): 3" x 5"
Distributed Weight	250.75 lbs/tire
Approximate Downforce	16.71 psi/tire
Length	80" without handle attached 111" with handle attached
Height	57"
Platform Height	24"
Ground Clearance	5.5"
Platform Size	46" x 78"
Payload Capacity	900 LBS
Warranty	Manufacturer's limited warranty covers any defect in workmanship or materials for one year from date of purchase.

No substitute for the original-The ONLY fall arrest cart with a locking engagement arm that ensures your anchor point is locked in its deepest point of penetration during a fall. The TriRex™ incorporates a streamlined design with a three-point front axle locking mechanism. Keep your workers safe and mobile with the TriRex™. The TriRex™ meets and exceeds OSHA 1926.502(d) & ANSI/ASSE Z359.6-2009.

Add-On Options

RAPTOR RESCUE™

Fall retrieval system provides for prompt rescue of fallen workers.

RMS-000-16



RAPTOR ALERT™

Fall warning system includes 130 decibel siren and strobe light.

RAS-000-11



SLR TRAY

For upright positioning of SRL's off the roof surface.

SLR-000-13



ICE Platform

A place for everything you need in case of emergency. Can be ordered fully stocked: Storage for 6 fire extinguishers, 1 five gallon water cooler, first aid kits, and any other safety supplies your jobsite requires.

ICE-PE-000-12 (stocked)

ICE-P-000-12 (empty)



Vinyl Cover

Protects the TriRex™ from the elements when not in use.

TR-VC-000-13



10ft³ Job Box

Part# JB-05-000

Dimensions 24"l x 31.5"w x 24"h

Capacity 10 cubic feet

Weight 77 LBS

20ft³ Job Box

Part# JB-04-000-11

Dimensions 47.5"l x 30"w x 24"h

Capacity 20 cubic feet

Weight 140 LBS

Key Features

• Up to 5 workers

(3 fall arrest & 2 on fall restraint simultaneously)

- Works on concrete*
(*Max 2 person fall arrest)

- Widest array of approved working surfaces in the industry
- Patented ratchet-locking engagement claw
- Fail-safe design
- Built in ballast

- No assembly required
- Built in fork pockets
- 4 corner lifting guide rings
- Removable height adjustable locking handle
- Optional fall rescue device
- Flat free polyurethane tires



sales@leadingedgesafety.net