



TRIREX

Mobile Fall Protection



www.leadingedgesafety.net
(888) 990.2990

TR-000-03-20 with single 20ft³ Job Box

Product Information

Fall Arrest Capacity	Three Workers
Fall Restraint Capacity	Two Workers (Maximum Fall Arrest & Restraint capacities may be used simultaneously.)
Net Weight	1180 LBS
Tires	8.5" x 18" Solid Polyurethane 15 in ² calculable surface area): 3" x 5"
Distributed Weight	250.75 lbs/tire
Approximate Downforce	16.71 psi/tire
Length	80" without handle attached 111" with handle attached
Height	57"
Platform Height	24"
Ground Clearance	5.5"
Platform Size	46" x 78"
Payload Capacity	900 LBS
Warranty	Manufacturer's limited warranty covers any defect in workmanship or materials for one year from date of purchase.

No substitute for the original—The ONLY fall arrest cart with a locking engagement arm that ensures your anchor point is locked in its deepest point of penetration during a fall. The TriRex™ incorporates a streamlined design with a three-point front axle locking mechanism. Keep your workers safe and mobile with the TriRex™. The TriRex™ meets and exceeds OSHA 1926.502(d) & ANSI/ASSE Z359.6-2009.

Add-On Options

RAPTOR RESCUE™

Fall retrieval system provides for prompt rescue of fallen workers.
RMS-000-16



RAPTOR ALERT™

Fall warning system includes 130 decibel siren and strobe light.
RAS-000-11



SLR TRAY

For upright positioning of SRL's off the roof surface.
SLR-000-13



ICE Platform

A place for everything you need in case of emergency. Can be ordered fully stocked: Storage for 6 fire extinguishers, 1 five gallon water cooler, first aid kits, and any other safety supplies your jobsite requires.

ICE-PE-000-12 (stocked)

ICE-P-000-12 (empty)



Vinyl Cover

Protects the TriRex™ from the elements when not in use.

TR-VC-000-13



Key Features

- **Up to 5 workers (3 fall arrest & 2 on fall restraint simultaneously)**
- Works on concrete* (*Max 2 person fall arrest)
- Widest array of approved working surfaces in the industry
- Patented ratchet-locking engagement claw
- Fail-safe design
- Built in ballast
- Flat free polyurethane tires
- No assembly required
- Built in fork pockets
- 4 corner lifting guide rings
- Removable height adjustable locking handle
- Optional fall rescue device

20ft³ Job Box

Part# JB-04-000-11

Dimensions	47.5" w x 30" d x 24" h
Capacity	20 cubic ft
Weight	140 LBS