



# Fall Arrest Ratings on Approve Surfaces

## Safety Bull™ Mobile Fall Protection

ANSI/ASSE Z359.6-2009 / OSHA 1926.502(d)(15)

2 Man Fall Arrest

***THE SAFETY BULL™ HAS BEEN TESTED AND APPROVED FOR THE FOLLOWING SUBSTRATES:***

BUILT-UP ROOFING (BUR) <sup>2</sup>	MODIFIED BITUMEN <sup>2</sup>
THERMOPLASTIC POLYOLEFIN (TPO) <sup>2</sup>	ETHYLENE PROPYLENE DIENE MONOMER (EPDM) <sup>2</sup>
POLYVINYL CHLORIDE (PVC) <sup>2</sup>	BALLASTED SINGLE-PLY MEMBRANES <sup>2</sup>
BUILT-UP ROOFING (BUR) AND GRAVEL <sup>2</sup>	INVERTED ROOF MEMBRANE ASSEMBLY (IRMA) <sup>2</sup>
ROOF COATINGS <sup>2</sup>	

PLYWOOD	HIGH DENSITY FIBERBOARD <sup>1,4</sup>
DENSDECK® <sup>1,4</sup>	GYPSUM BOARD <sup>1,4</sup>
POLYISOCYANURATE (ISO) <sup>1,4</sup>	EXPANDED POLYSTYRENE (EPS) <sup>1,4</sup>
EXTRUDED POLYSTYRENE (XPS) <sup>1,4</sup>	SPRAY-APPLIED POLYURETHANE <sup>1,4</sup>
INSULATING LIGHTWEIGHT CONCRETE <sup>5,6</sup>	

METAL DECK (24GA - 20GA)	STRUCTURAL LIGHTWEIGHT CONCRETE <sup>5,6</sup>
CONCRETE DECK <sup>5,6</sup> (4000-6000PSI)	TOPSOIL—COMPACTED
GYPSUM DECK <sup>5,6</sup>	ASPHALT PAVEMENT
GRAVEL—COMPACTED	

FLAT SURFACES AND UP TO 2:12 SLOPE.

**DO NOT USE THE SAFETY BULL™ ON THE FOLLOWING SUBSTRATES:**

- ICE
- SNOW
- TECTUM DECK
- METAL DECKS LESS THAN 24GA OR GREATER THAN 20GA

1 WHEN MECHANICALLY FASTENED OR ADHERED TO AN APPROVED SUBSTRATE.  
 2 WHEN USED AS PART OF A COMPLETE ROOF ASSEMBLY.  
 3 SUBSTRATE IS ALLOWABLE WHEN COVERED WITH 3/4" PLYWOOD SECURED WITH A MINIMUM OF EIGHT (8) FASTENERS. FIG 1-2  
 4 SUBSTRATE IS ALLOWABLE WHEN TOTAL INSULATION THICKNESS IS GREATER THAN 3.875" OR USED WITH AN APPROVED METAL DECK.  
 5 WHEN EUROPEAN STANDARDS APPLY DIN EN 795:2012, DIN CEN/TS 16415:2017 REDUCE THE MAXIMUM NUMBER OF USERS IN FALL ARREST TO 1 (ONE)  
 6 ADDITIONAL WEIGHT PACKAGE MUST BE INSTALLED TO COMPLY WITH THIS SUBSTRATE

DensDeck® is a registered trademark of Georgia-Pacific Gypsum, LLC.