

# MGT 6

## Protector for unpolished surfaces

Full saturation water and oil repellent sealer for sandstone, marble, granite, natural stone, marble or cement agglomerates with rough, sandblasted, bushhammered, flamed finish. Does not change the natural colour of the material.

Penetrates into the porosity without leaving surface residues; does not turn yellow. Protects the surfaces from staining substances like oil, coffee, grease. Specific for kitchen countertops, tables, floors and coatings.

### Strong Points

- Antistain
- Antioil
- Water repellent
- Does not turn yellow
- Does not change the colour of the surface
- Reversible
- Not film forming
- Makes the cleaning easier
- Excellent on kitchen countertops

### Application

#### SHAKE BEFORE USING

READY TO USE PRODUCT, DO NOT DILUTE.

On clean and dry surfaces apply MGT 6 directly, spreading it out evenly with a mop or a microfiber cloth with circular motions.

Depending on the absorption apply 2 or 3 coats at a distance of 4-6 hours one from the other.

In case of very rough apply with a low pressure gun and spread it out evenly with a microfiber cloth.

Allow to dry before walking on the surface.

Wait at least 48/72 hours before carrying out staining tests, so to allow the product to dry even in the porosity of the surface.

For the ordinary maintenance of the treated surface we recommend the regular use of MGP 24 detergent.

### Warnings

Before using the product, read the toxicological data sheet (MSDS) and the label detailing all risks and the personal protective equipment to be used for a correct use. The data of this technical data sheet is based on reliable information. Despite of this, the manufacturer can't know in advance the condition of the materials to be processed and the way of use of the product. Therefore, he disclaims any and all responsibility for damage arising from inadequacy of the product for special applications.

Before treating or cleaning surfaces, carry out a test on an invisible point to prevent possible damages, since our responsibility is limited to the warranty of the purchased product and therefore we disclaim any responsibility for damages resulting from negligence or wrong use.

### Packaging and Storage

Keep the original, sealed container in covered, ventilated, dry environment and keep away from heat or low temperatures. After the use keep the package well closed, so the product has a shelf life of approx. 36 months.

Box of 15 x 1 litre bottle – Box of 4 x 5 liter cans



Coverage: **Rough surfaces:** 1 litre for approx. 10- 12 m2 depending on the finish of the surface and on its absorption.

**Honed surfaces:** 1 litre for approx. 12-18 m2 depending on the finish of the surface and on its absorption.



MASSIMO PIRACCINI srl

Legal seat: Via Santa Croce 477 – 47032 Bertinoro (FC) Italy

Management unit: Via M. Uccellini 22 – 47034 Forlimpopoli (FC) Italy

Tel. +39 0543 745268 Fax +39 0543 745644

www.mptreatment.com italia@mptreatment.com export@mptreatment.com

