

CODE TOILET SUITES, PANS

BPIR DECLARATION

VERSION: V1

DESIGNATED BUILDING PRODUCT: CLASS 1

Declaration

ELITE BATHROOMWARE LTD has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product / System

Name	Code Toilet Suites, Pans
Line	Vitreous China toilets suites
Identifier	All Code Toilet Ranges

Description

• All Code Toilets are suitable for domestic or commercial use • All Code toilets are available in White Gloss. Selected ranges are available in Matte White & Matte Black • All Code toilets comply with the Wels scheme. (Water efficiency labelling scheme) AS/NZS6400 4.5L/3L flush. • All Code toilets are made from Vitreous China

Scope of use

• All Code Toilets are designed to be installed in residential or commercial bathrooms • All White Gloss Toilets can be installed bottom or top inlet entry • All Matte White & Matte Black toilets can be installed top inlet entry only • Code toilets are available in floor or wall hung models • All Code toilets can be used for low pressure systems

Conditions of use

• Floor Pan weight must not exceed 400kg (as per Watermark testing AS1172.1) • According to the AS/NZS3500 Plumbing Regulations, it is recommended to install inline filters and pressure limiting valves (PLV) with a pressure limit of 500kpa at each premises. This installation is crucial to safeguard the longevity of valves and washers. • Must be installed by a registered plumber • Refer to the manufacturer's cleaning maintenance guide • Cannot be installed in areas with high levels of hardness of water

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.2

Contributions to compliance

B2.3.1(a) (ii) and (iii) as well as B2.3.2: Code toilet suites are designed to maintain durability for a minimum of 10 years, provided they are not subjected to crushing or impact that could lead to the vitreous china cracking and causing water leakage. The floor pans of these fixtures have undergone testing to ensure they can withstand a weight of 400kg. When handled and used correctly, code toilets are deemed safe, adhering to a weight-bearing capacity of up to 400kg. refer to installation guide for more information

F2.3.1: Not Applicable

G1: Complies with WELS regulations AS/NZS6400

Supporting documentation

The following additional documentation supports the above statements:

None added

For further information supporting Code Solid Surface Basin claims refer to our website.

Contact Details

Manufacture Location	Overseas
Legal and trading name of manufacturer	SENYUAN WOOD
Legal and trading name of importer	ELITE BATHROOMWARE LTD
Importer address for service	59A Allens Road, East Tamaki 1072
Importer website	https://www.elitebathroomware.co.nz/
Importer NZBN	9429036523320
Importer email	marketing@elitebathroomware.co.nz
Importer phone number	092747030

ELITE BATHROOMWARE LTD

59A Allens Road, East Tamaki 1072 New Zealand
092747030 | <https://www.elitebathroomware.co.nz/>

APPENDIX

NOTE: THE BELOW APPENDIX INCLUDES INFORMATION RELATING TO BPIR READY. PUBLISHING THIS INFORMATION IS NOT A REQUIREMENT UNDER BPIR. ITS INCLUSION HERE IS TO PROVIDE A REFERENCE FOR HOW THIS BPIR SUMMARY WAS GENERATED AS WELL AS TO HELP SUMMARY CREATORS UNDERSTAND THE PERFORMANCE CLAUSES SUGGESTED BY BPIR READY.

BPIR Ready selections

Category: Basins, baths and bidets

YES NO

Suitable for accessible facilities



Building code performance clauses

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c) 5 years if: the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and failure of those building elements to comply with the building code would be easily detected during normal use of the building.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

1. facilitate sanitation,
2. avoid risk of food contamination,
3. avoid harbouring dirt or germs,
4. provide appropriate privacy,
5. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
6. allow effective cleaning,
7. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
8. provide a healthy safe disposal system when non-water-borne disposal is used.

G12 Water Supplies

G12.3.2

A potable water supply system must be—

1. protected from contamination; and
2. installed in a manner that avoids the likelihood of contamination within the system and the water main; and
3. installed using components that will not contaminate the water.