

# POS PRINTER

## SLK-T20EB II

- Energy star qualified for power efficiency
- High speed printing : Max. 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Accessories : Melody box, spillproof cover
- Wall mount installation available



### APPLICATIONS



Shopping



Mart



Airport



Hospital



Coffee Shop



Bank



Restaurant



Ticketing



Parking




Lottery



Election

EASY-LOAD DESKTOP THERMAL POS PRINTER

# SLK-T20EB II



MODEL		SLK-T20EB II
PRINTING	METHOD	Direct Thermal
	SPEED	Max. 220mm/sec
	WIDTH	72mm
	RESOLUTION	180DPI / 203DPI(Optional)
PAPER	TYPE	Thermal Receipt Paper / Linerless(Optional)
	WIDTH	50mm ~ 82.5mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. $\varnothing$ 80.0mm
	ROLL CORE INNER	12.5mm $\pm$ 0.5mm
RELIABILTY	TPH LIFE	160km
	MCBF	60,000,000Lines
AUTO CUTTER		1,800,000cuts(Guillotine)
SENSOR	STANDARD	Paper End, Paper Low, Cover Open
	OPTION	Black Mark
INTERFACE		USB (B type) + Ethernet + Serial Built-in
EMULATION		ESC/POS Command Compatible
DRIVER		Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit) Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 1.75A
TEMPERATURE	OPERATION	0 ~ 45°C
	STORAGE	-20 ~ 60°C
DIMENSION		152 x 204 x 150 mm (W x D x H )
WEIGHT		1.7kg
COLOR		Cool grey, Ivory

## INTERFACE



## ACCESSORY



Spill proof cover



Melody box



J. STEPHEN Lab., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210 Republic of Korea

T.+82-31-8077-5000 F.+82-31-459-8880

www.miniprinter.com

