



Thermal Receipt Printer

XS300L Series



- Easy drop-in paper loading.
- 300mm per second high printing speed.
- Improved cover design for increased spill resistance.
- Handles 80mm or 58mm paper roll sizes.



XS300L Series Thermal Receipt Printer



Model	XS300L Series
Printing method	Direct thermal
Print speed	300 mm/s Max.
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Paper width	57.5±0.5mm/79.5±0.5mm
Column Capacity	576 dots/line(adjustable by command)
Interfaces	USB+Serial+Lan+RJ45
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns / Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)
Cutter	
Auto cutter	Partial
Barcode character	
Extension character sheet	PC347 (Standard Europe) , Katakana, PC850 (Multilingual) , PC860 (Portuguese) , PC863 (Canadian-French) , PC865 (Nordic) , West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2) , PC852 (Latin2) , PC858, IranII, Latvian, Arabic, PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR Code / PDF417
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100-240V, 50 ~ 60Hz Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	0.89 KG
Dimensions	170.8*131.4*111mm (L*W*H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/ Android/ Windows



www.VisionTechShop.com
Address : 100 Temple Ave. Hackensack, NJ 07601
Tel. +201.679.7793