



MARINAFLEXX AUFBAUCHART BAD

Stand 17.03.2022



LIZIN UTZ[®]
YOUR FLOOR. OUR PASSION.

MARINAFLEXX PARKETTODEN BAD



Verkleben des Marinaflexx Parketts mit UZIN MK 92 S / MK 250 – Verbrauch ca. 1000 – 1200 g/m²,
Zahnung B 11



Fugendichtband und Dichtecken DB 140 Slim kleben mit Codex SK 100, 1-K Hybrid Dicht- und Montagekleber



Codex Hydrostop Abdichtungs- und Entkopplungsbahn kleben mit UZIN MK 92 S, Zahnung B 2, ca. 900 g/m²



Grundieren des Untergrundes mit UZIN PE 414 BiTurbo / PE 412, Nylon Plüsch Walze – 150 g/m²



Schleifen & Saugen des Untergrundes

KONTAKT PERSONEN



ULRICH WENG

Leiter UZIN Anwendungstechnik Innendienst

T +49 731 4097-265

ulrich.weng@uzin-utz.com

ROBIN GABEL

Technischer Kundenservice UZIN

T +49 731 4097-260

robin.gabel@uzin-utz.com

LIZIN LITZ®

YOUR FLOOR. OUR PASSION.

UZUN®

WOLFF®

PALLMANN®

arturo®

codex®

Pajarito®



MARINAFLEXX SETUP CHART BATHROOM

State 17.03.2022



LIZIN UTZ®
YOUR FLOOR. OUR PASSION.

MARINAFLEXX PARQUET FLOOR BATHROOM



glue the marinaflexx parquet with UZIN MK 92 S / MK 250 – consumption approx 1000 – 1200 g/m², perforation B 11



glue joint sealing tape and sealing corners DB140 Slim with Codex SK 100, 1-K Hybrid Sealing and assembly adhesive



glue Codex Hydrostop waterproofing and decoupling membrane with UZIN MK 92 S, perforation B 2, approx 900 g/m²



primeing of the substrate with UZIN PE 414 BiTurbo / PE 412, nylon plush roller – 150 g/m²



sanding and vacuuming of the substrate

CONTACT



ULRICH WENG

Head UZIN application technology back office

T +49 731 4097-265

ulrich.weng@uzin-utz.com

ROBIN GABEL

technical customer service UZIN

T +49 731 4097-260

robin.gabel@uzin-utz.com

LIZIN LITZ®

YOUR FLOOR. OUR PASSION.

UZUN®

WOLFF®

PALLMANN®

arturo®

codex®

Pajarito®