

# SAFETY DATA SHEET NPN# 80104504

Date of Preparation: Aug. 29, 2020

	Section 1: IDENTIFICATION
Product Name:	Eco Sanitizer Wipes
Synonyms:	Not available.
Product Use:	Hand and Surface Cleaner.
<b>Restrictions on Use:</b>	Not available.
Manufacturer/Supplier:	Eco Sanitizer
	7664 Winston Street, Burnaby B.C. V5A 2H4
Phone Number:	1-604-339-0965
Emergency Phone:	1-888-326-5029
	CANUTEC: 1-888-CAN-UTEC (226-8832), 613-996-6666
Date of Preparation of SDS:	Aug 29, 2020

#### Section 2: HAZARD(S) IDENTIFICATION

#### **GHS INFORMATION**

Classification: Flammable Liquids, Category 2

Eye Irritation, Category 2A

Specific Target Organ Toxicity (Single Exposure), Category 3 - Narcotic Effects LABEL ELEMENTS Hazard Pictogram(s):



Signal Word:DangerHazardHighly flammable liquid and vapor Causes serious eye irritation. May causeStatements:drowsiness or dizziness.

# Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep the container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating, and lighting equipment.

Use non-sparking tools. Take action to prevent static discharges.

Avoid breathing mist, vapours, or spray.

Wash thoroughly after handling.

Wear protective gloves, protective clothing and eye protection.

 Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor if you feel unwell.



Date of Preparation: Aug. 29, 2020

If eye irritation persists: Get medical attention.

In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish.

**Storage:** Store in a well-ventilated place. Keep the container tightly closed. Keep cool.

**Disposal:** Dispose of contents and container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200). This material is considered hazardous by the Hazardous Products Regulations.

#### Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% vol./vol.
Ethanol	Not available.	64-17-5	70
Hydrogen peroxide (H2O2)	Hydrogen peroxide	7722-84-1	0.1 - 1
Non-Hazardous Ingredient(s)	Common nome / Synonyme	CAS No.	% vol./vol.
Non nazardous ingredient(s)	Common name / Synonyms	CA5 NO.	% VOI./VOI.
Water	Not available.	7732-18-5	10 - 30

Section 4: FIRST-AID MEASURES

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately.

Acute and delayed symptoms and effects: May cause drowsiness or dizziness. May cause respiratory irritation. Signs/symptoms may include



Date of Preparation: Aug. 29, 2020 cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.

 Eye Contact:
 If in eyes: Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Acute and delayed symptoms and effects: Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Ethanol may cause painful sensitization to light, chemical conjunctivitis and corneal damage.

Skin Contact: If used as recommended, no first-aid measures are necessary. If in contact with large amounts of product: Rinse skin with water or shower. Call a poison center or doctor if you feel unwell.

Acute and delayed symptoms and effects: No adverse effects are expected under normal conditions of use. Handling of large amounts may cause skin dryness and/or irritation.

Ingestion: If swallowed: Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately.

Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately.

# Section 5: FIRE-FIGHTING MEASURES

# FLAMMABILITY AND EXPLOSION INFORMATION

Highly flammable liquid and vapor. Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to the source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when



Date of Preparation: Aug. 29, 2020

heated. Liquid is lighter than water.

If a tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

Fire involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of the tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from the area and let fire burn.

Sensitivity to Mechanical Impact:This material is not sensitive to mechanical impact.Sensitivity to Static Discharge:Take action to prevent static discharges. This material is<br/>sensitive to static discharge.

# MEANS OF EXTINCTION Suitable Extinguishing Media:

Small Fire: Dry chemical, CO2, water spray or alcohol-resistant foam.

Large Fire: Water spray, fog or alcohol-resistant foam. Move containers from the fire area if you can do it without risk.

# Unsuitable Extinguishing Media:

Do not use straight streams. CAUTION: This product has a very low flash point: Use of water spray when fighting fire may be inefficient.

Products of Combustion: Oxides of carbon. Acrolein.

**Protection of Firefighters:** Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

# Section 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded.



SAFETY DATA SHEET Personal Precautions:	Date of Preparation: Aug. 29, 2020 Do not touch or walk through spilled material. Use personal protection recommended in Section 8
Environmental Precautions:	Prevent entry into waterways, sewers, basements or confined areas
Methods for Containment:	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors
Methods for Clean-Up:	Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material.
Other Information:	See Section 13 for disposal considerations.

#### Section 7: HANDLING AND STORAGE

**Handling:** Do not swallow. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep the container tightly closed. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist, vapours, or spray. Wash thoroughly after handling. See Section 8 for information on Personal Protective Equipment.

**Storage:** Store in a well-ventilated place. Keep the container tightly closed. Keep cool. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

# Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

# **Exposure Guidelines**

# Component

Ethanol [CAS No.64-17-5]

ACGIH: 1000 ppm (TWA); A3 (2008) OSHA: 1000 ppm (TWA), 1900 mg/m3 (TWA);

Hydrogen peroxide [CAS No.7722-84-1]

ACGIH: 1 ppm (TWA); A3 (1990)

**OSHA:** 1 ppm (TWA), 1.4 mg/m3 (TWA);

Water [CAS No.7732-18-5]



Date of Preparation: Aug. 29, 2020

**ACGIH:** No TLV established. **OSHA:** No PEL established.

Glycerin [CAS No.56-81-5]

ACGIH: No TLV established.


**OSHA:** 15 mg/m3 (Total particulate) (TWA), 5 mg/m3 (Respirable fraction) (TWA); 10 mg/m3 (Total particulate) (TWA) [Vacated];

**PEL:** Permissible ExposureLimit **TLV:** Threshold Limit Value **TWA:** Time-Weighted Average

#### **Engineering Controls:**

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits. Use explosion-proof electrical, ventilating, and lighting equipment.

# PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection:	Wear chemical safety goggles when handling large amounts of products. Ensure that eyewash stations are close to the workstation location. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3-92 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.
Hand Protection:	Wear protective gloves when handling large amounts of product. Consult manufacturer specifications for further information.
Skin and Body Protection:	Wear protective clothing when handling large amounts of product. Flame resistant clothing that meets the NFPA 2112 and CAN/CGSB 155.20 standards is recommended in areas where material is stored or handled.
Respiratory Protection:	Not necessary under normal conditions of use. If handling large amounts of product, if engineering controls and ventilation are not sufficient to control exposure to below the



SAFETY DATA S	SHEET
---------------	-------

Date of Preparation: Aug. 29, 2020

allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-11, with organic vapor cartridge, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

#### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear	liquid.
-------------	-------	---------

Colour: Colourless.

Odour: Alcohol.

Odour Threshold: Not available.

Physical State: Liquid.

pH: Not available.

Melting Point / Freezing Point:Not available

Initial Boiling Point: 78 °C (172.4 °F) (Ethanol)

Boiling Range: Not available.

Flash Point: 12 °C (53.6 °F) (Closed Cup - Ethanol)

Evaporation Rate: Not available.

Flammability (solid, gas): Not applicable.

Lower Flammability Limit: Not available.

Upper Flammability Limit: Not available.

Vapor Pressure: Not available.

Vapor Density: Not available.

Relative Density: Not available.

Solubilities: Miscible in water.



Partition Coefficient: n- Octanol/Water: Not available

Auto-ignition Temperature: 400 °C (752°F) (Ethanol)

Decomposition Temperature: Not available

Viscosity: Not available.

Percent Volatile, wt. %: Not available.

VOC content, wt. %: Not available.

Density: 0.8594 Kg/L at 20 °C

**Coefficient of Water/Oil Distribution:** Not available

#### Section 10: STABILITY AND REACTIVITY

Reactivity: Contact with incompatible materials. Sources of ignition. Exposure to heat.

Chemical Stability: Stable under normal storage conditions.

Possibility of Hazardous Reactions: None known.

Conditions to Avoid: Contact with incompatible materials. Sources of ignition. Exposure to heat.

Incompatible Materials: Acids. Strong oxidizers.

Hazardous Decomposition Products: Not available.

#### Section 11: TOXICOLOGICAL INFORMATION

#### EFFECTS OF ACUTE EXPOSURE Product Toxicity Oral: Not available.

Dermal: Not available. Inhalation: Not available.

. \_ . .

Component T	Toxicity			
Component	CAS No.	LD <sub>50</sub> oral	LD50 dermal	LC50
Ethanol Hydrogen	64-17-5	7060 mg/kg (rat)	20000 mg/kg (rabbit)	20000 ppm (rat); 10H
peroxide	7722-84-1	376 mg/kg (rat)	4060 mg/kg (rat)	2000 mg/m3 (rat); 4H

Date of Preparation: Aug. 29, 2020



Water 7732-18-5 Not available. Glycerin 56-81-5 12600 mg/kg (rat)

Date of Preparation: Aug. 29, 2020 Not available. > 10000 mg/kg (rabbit)

> 90000 µl/kg (rat); 4H > 570 mg/m3 (rat); 1H

Likely Routes of Exposure: Target Organs:

Eve contact. Skin contact. Inhalation. Ingestion. Skin absorption. Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood. Kidneys. Central nervous system.

# Symptoms (including delayed and immediate effects)

Inhalation: May cause drowsiness or dizziness. May cause respiratory irritation.

Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.

Eye: Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Ethanol may cause painful sensitization to light, chemical conjunctivitis and corneal damage.

Skin: No adverse effects are expected under normal conditions of use. Handling of large amounts may cause skin dryness and/or irritation.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization: Not available.

**Respiratory Sensitization:** Not available.

Medical Conditions Aggravated By Exposure: Not available

# EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs:	Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood.		
	Cardiovascular system. Liver. Kidneys. Reproductive system. Central		
	nervous system.		

- Prolonged or repeated contact may dry skin and cause irritation. High **Chronic Effects:** vapour concentrations, generally greater than 10% by volume, may sensitize the heart and lead to lethal cardiac arrhythmias.
- Carcinogenicity: Product is not classified as a carcinogen. See Component Carcinogenicity table below for information on individual components. Animal studies with Ethanol have reported the development of tumours.

# **Component Carcinogenicity**

Component	ACGIH	IARC	NTP	OSHA	Prop 65
Ethanol	A3	Group 1	Not listed.	OSHA Carcinogen.	Not listed.



SAFETY DATA SHEETDate of Preparation: Aug. 29, 2020Hydrogen peroxideA3Group 3Not listed.Not listed.Not listed.Not listed.Not listed.Not listed.

Mutagenicity: Laboratory experiments with Ethanol have resulted in mutagenic effects.

Reproductive Effects: Ethanol may cause reproductive effects.

Developmental Effects Teratogenicity: Not available.

Embryotoxicity: Ethanol has been shown to produce fetotoxicity in the embryo or fetus of laboratory animals if swallowed. Prenatal exposure to ethanol by ingestion is associated with a distinct pattern of congenital malformations that have collectively been termed the "fetal alcohol syndrome".

Toxicologically Synergistic Materials: Not available.

# Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Other Adverse Effects: Not available.

# Section 13: DISPOSAL CONSIDERATIONS

**Disposal Instructions:** Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

#### Section 14: TRANSPORT INFORMATION

U.S. Department of Transportation (DOT) Proper Shipping Name: UN1170, ETHANOL, 3, PG II Class: 3 UN Number: UN1170 Packing Group: II Label Code:



PLAMMABLE LIQUID

Date of Preparation: Aug. 29, 2020

Canada Transportation of Dangerous Goods (TDG) Proper Shipping Name: UN1170, ETHANOL, 3, PG II

Class: 3 UN Number: UN1170 Packing Group: II Label Code:



Section 15: REGULATORY INFORMATION

#### Chemical Inventories US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

# Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

# Federal Regulations

# **United States**

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# SARA Title III

Component	Section	Section	CERCLA	Section	RCRA	CAA
	302 (EHS)	304 EHS	RQ (lbs.)	313	CODE	112( r ) TQ
	TPQ (lbs.)	RQ (lbs.)				(lbs.)
Hydrogen peroxide	e 1000	1000	Not listed	. Not listed	l. Not lis	sted. Not listed.

# State Regulations

**Massachusetts** US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Component	CAS No.	RTK List
Ethanol	64-17-5	Listed.
Hydrogen peroxide	7722-84-1	Е
Glycerin	56-81-5	Listed.



**Note:** E = Extraordinarily Hazardous Substance

Date of Preparation: Aug. 29, 2020

**New Jersey** US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

Component	CAS No.	RTK List
Ethanol	64-17-5	SHHS
Hydrogen peroxide	7722-84-1	SHHS
Glycerin	56-81-5	Listed.

Note: SHHS = Special Health Hazard Substance

**Pennsylvania** US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component	CAS No.	RTK List
Ethanol	64-17-5	Listed.
Hydrogen peroxide	7722-84-1	Е
Glycerin	56-81-5	Listed.

**Note:** E = Environmental Hazard

# California

California

Prop 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

# Section 16: OTHER INFORMATION

**Disclaimer:** The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

**Date of Preparation of SDS:** August 29, 2020 **Version:** 1.0

GHS SDS Prepared by: Deerfoot ConsultingInc.

Phone: (403) 720-3700