


Bocaro Charge BASIC

811324 |



Charging bollard
4051859971061
D 180, H 1150



Charging column with square cross section. With EV charger to IEC 61851-1 Mode 3. For private applications. Luminaire tube made of corrosion resistant aluminium with pressure die-cast aluminium cover, seawater resistant powder-coated. With fully enclosed stainless steel mounting base. Stainless steel bracket and screws for EV charger unit. Elongated holes in base for easy bollard alignment. EV charger in integrated compartment with one type 2 charging socket, lockable.

Colour

Colour anthracite metallic

Dimensions

Diameter D 180 mm
Height H 1.150 mm
Weight 18,1 kg

Electrical

Voltage	/ 50 Hz
Number of charging units	1
Max. power per charging point	22
Number of vehicle connectors	
Type 2	1
Earth leakage circuit breakers	
Type A/LS	1
Charging cable lockable	no
DC residual current detection	yes
Protective contact 1	no
Protective contact 2	no
With circuit breaker	no
Network-enabled as a master	yes
Network-enabled as an extender	yes
Networkable via LAN	yes
Networkable via Wi-Fi	no
Radio standard LTE	no
Radio standard 5G	no
With energy meter	no
With key switch	no
With built-in RFID card reader	yes
NFC (Near Field Communication)	no
Static load management	yes
Dynamic load management	yes
Ocpp version	1.6
Plug and charge (ISO 15118)	yes
With display	no
Compatible Apple HomeKit	no
Compatible Google Assistant	no
Compatible Amazon Alexa	no
IFTTT support available	no
Operation and configuration by app	yes
Export of charging logs	yes
Backend included	yes
With MID compliant energy meter	yes
Installation side connection model	3-phase
Input voltage	400 V

Bocaro Charge BASIC

811324 |



Connectable conductor cross
section 6

Approbations

Protection class I
Conformity mark CE

Accessories

983019.000