


# LUPALO POLLER

982705.004 | Bollards



Bollards  
4051859566977  
LED  
D 187, H 326



Bollard luminaire head for public sector applications. Luminaire head made of corrosion resistant die-cast aluminium, seawater resistant powder-coated, stainless steel screws. Diffuser: glass, transparent. Multi-chip LED with high-performance refractor optics. Symmetrical light distribution Fastening of the luminaire head to a tube via a bayonet. Elegant-looking power supply via delicate steel cables between converter and LED. In order to fit the luminaire head, please order the required luminaire tube separately. Please order fuse box separately.

## Electrical

Control gear	DALI
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	18
Luminaires on B16A fuse	28
System power	36 W
Luminaire efficacy	108
Inrush current / Inrush current duration	26 A / 180 $\mu$ s
Total harmonic distortion	10 %

## Colour

Colour	silver metallic
--------	-----------------

## Dimensions

Diameter D	187 mm
Height H	326 mm
Weight	3,71 kg

## Lamp

Lamp	LED
Colour temperature	3000K
Colour rendering index (CRI)	70
Colour tolerance	5
Rated life	100000 h (L80/B10)
Photobiological safety according to EN 62471	Risk group 2

## Lighting technology

Luminous flux component in the upper half-space	0
CIE Flux Code / CEN Flux Code	11 42 92 100 100
Colour temperature	3.000 K
Rated luminous flux	3.900 lm
Beam angle Down	152°
Beam angle combined Up	0°
Glare evaluation UGR (4H 8H)	30,2

## Approbations

Type of protection	IP 65
Protection class	II
Conformity mark	CE